

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 4 and 5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Pages 7151-52)

-----  
Set ¼ sec. post at average distance, from which  
A B.Oak 14" dia., bears N.65°E., 137 lks. dist.  
A W.Oak 8" dia., bears S.53°W., 137 lks. dist.

M. B. Germond, Wit: F.C. Frear and Hank Weaver - May 1917 - (Probably from survey recorded in Field Book 42 Pg. 27+; Vol. 3 Pg. 42; C.S. File 7/9 and M 1-35, but, the corner wording is from "old" Cor. Bk. Pg. 145)

-----  
I find one old bearing tree and set in a new corner which is a 3/4" x 24" galv. I.P. from which  
A W.Oak 5" dia., bears S.15°30'E., 23 2/3 lks.  
A W.Oak 13" dia., bears S.46°18'W., 272.6 lks.

Doug. County Surveyors Office - John Powell and crew - Jan. 1970 - C.S. File 53/26-48

-----  
Found - 3/4" I.P. at corner.  
5" W.Oak now 10", S.15½°E., 15.6 ft., opened & found scribe of (¼).  
13" W.Oak now 24" S.46¼°W., 179.6 ft. shows an axe face.  
Set B. cap at ¼ cor. mkd: County Surveyor's T30S R5W ¼ S5|S4 Office, 1969  
Set 3/4" I.P. alongside brass cap.  
New BTs -6" Laurel S.79½°E., 30.7 ft. scribed ¼ S4 CS BT.  
8" D.Fir S.88°W., 114.6 ft. scribed ¼ S5 CS BT.  
This ¼ cor. lies on a N. slope over looking populated area.

Fd. OK, Jan. 1986, K. Degroot, M 100-77 A&B  
Fd. OK, Sept. 1990, Land Partition, 1990-0080  
Fd. OK, Feb. 1992, G. Baughman, M 114-43