

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 337700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 33 only, T29-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6425)

Set 1/4 sec. post at proper distance, from which
A W. Oak, 10" dia., bears S.31°W., 32 lks.
A W. Oak, 12" dia., bears N.67°E., 39 lks.

G.L.O. Survey by Oscar F. Thiel, under Contract #658 dated May 21, 1896. (DCSO records Vol. 17 Page 7181)

Junction of 4 fences, begin ascent and enter oak timber. I made a careful search in this vicinity for the 1/4 Sec. cor., but could not find any trace of cor. post or witness trees, some stumps are left West of this point.
At the supposed 1/4 sec. cor. bet. secs. 4 & 33.

Doug. County Surveyors Office - James W. Byron, Co. Surveyor - John Powell & Crew - 3/1970 - C.S. File 54/108 - M 39-45

This corner set from survey at prorated distance.
Set - Brass cap at Cor. Mkd:

County Surveyor's T 29 S R 5 W
Office 1/4 S 33
1970 T 30 S

New BT's - 14" W. Oak, N.65°E., 85.5' mkd: "1/4 S33 CS BT"
18" B. Oak, N.12°W., 129.0' mkd: "1/4 S33 CKS BT"
This Corner lies 6.0' N of E-W fence line & 140.0' S of ravine

Found OK by William Ruppert - July 1991 - M 112-32.
Found OK by William Ruppert, Sept. 1992, M 115-70

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause - 2/7/2008 - C.S. File 67/25-8

Found - 2 1/2" dia., BC (properly mkd) on 1 1/4" O.D. iron pipe. BC/IP had been disturbed & leaned 0.8' westerly. All accessories missing due to excavation of new Subdivision lots to north.

New - Dug down & located plumb position of BC/IP, referenced this position, removed & reset BC/IP at referenced position. Stamped "RESET 2008" on BC. (MKD) COUNTY SURVEYORS OFFICE

T29S R5W
1/4 S .33
RESET
2008
T30S
1970

cont. next pg

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 337700

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 33 only; T29-5.

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

12" dia., W.Oak, double blazed & scribed "¼ S33 CS
BT" bears S.82¼°E., 30.0 ft.
Brass cap at N¼ cor. sec. 4 only bears Easterly
97.87 ft. See M39-45
No other accessories were created at this time.
BC/IP is shown on Village View Subd. Ph. 2
(unrecorded at this time) and will have direct
ties to other property corners in subd.
Compass decl. 16¼°E.