

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION S 1/4 Sec. 33 only

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7134)

Set ¼ sec. post at proper distance, from which
A pine, 30" dia., bears S.29°W., 100 lks.
A R.Fir, 10" dia., bears N.23°E., 62 lks.

Raymond Brown - For: Cow Creek Band of Umpqua Tribe of Indians - 10/2013 - M166-4

SET - 2"x36" iron pipe with 3" brass cap attached, mkd. "PLS2391,T30S., R5W., 114S33, 2013" from which Existing a 36" fir bears S.25°E., 72' with healed blaze (existing BT for North ¼ of section 4 only).
A truck axle (no record) bears N.10°30'W., 3.09'
A brass cap for north ¼ corner sec. 4 only bears S.89°44'04"W., 43.58'
NEW - A 8" fir bears N.85°E., 21.5', mkd. S. ¼ S33 BT.
A 10" Madrona bears S.20°30'W., 8.3', mkd. S ¼ S33 BT.
A 8" Madrona bears N.7°16'W., 43.8', mkd. S ¼ S33 BT.
A 8" Madrona bears N.28°30'E., 58.9', mkd. S ¼ S33 BT.

Fd. BC, Axle & BOs per renewal notes by Ron Quimby - Nov. 2014 - M166-22