

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 28

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7149)

-----

Set ¼ sec. post at average distance, from which  
A B.Oak 6" dia., bears N.2°E., 30 lks. dist.  
A W.Oak 5" dia., bears S.60°E., 75 lks. dist.

---

E. Summers - For: Bollenbaugh Estate - April 2, 1920 (No record source found for this language except "old" Cor. Bk. Pg. 146)

-----

Reset from old BTs. Set stone, from which new BTs bear as follows:  
A W.Oak 6" dia., bears N.21°E., 30 lks.  
A B.Oak 10" dia., bears S.35°W., 85 lks.

---

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - 10/12/2012 - C.S. File 67/36-44

-----

Reported as not found.  
Search area determined by GPS (Trimble GEO XT) ties to nearest fd Gov. cors. falls in deeply excavated building site. No native ground remains; no monument fd.  
Search area for all BTs (determined as above) also falls in excavated area. No BT evidence remains.