

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7151)

Set ¼ sec. post, at average distance, from which
A B.Oak 10" dia., bears S.27°E., 125 lks.
A B.Oak 15" dia., bears N.43°W., 85 lks.

No trace of the ¼ sec. cor. or its bearing trees to be found, fire appears to have been here at different time. - GLO survey by Oscar F. Thiel, under Contract #658 dated May 21, 1896 (DCSO records, Vol. 17 Page 7185-86)

BLM resurvey by Lynn Roseberry & James Jelley, under Group #662 -Surveyed Oct. 1967/June 1969 (DCSO records, Vol. 38 Page 15549)

(Point for the ¼ sec. cor. of sec. 16 only, at proportionate distance; there is no remaining evidence of the original corner. No permanent monument established. - this point is .15 ch, N.89°12'E of ¼ sec. 9)

Point for the ¼ sec. cor. of sec. 9 only, at proportionate distance and on the S. bdy. of sec. 9.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:
T 30 S R 5 W
¼ S 9
1969

from which
A Fir 13" dia., bears N.58°E., 17 lks. dist. mkd. ¼ S9 BT.
An Oak 10" dia., bears N.22½°W., 11 lks. mkd. ¼ S9 BT.

Fd. Ok by K DeGroot, 7/2006 - M146-42
Fd. Ok by D. Edwards 1/2008 - M154-73