

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 378100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4 only, T31-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W. P. Wright, under Contract #281 dated May 16, 1878 (DCSO records, Vol. 19 Page 7891)

Could find no evidence of survey.
Set a post for closing corner. Set post 6 x 6 ins. by 4 ft. long, 20" in ground, for corner to secs. 3 and 4, from which
A Fir 12" dia., bears N.24°E., 10 lks.
A Fir 6" dia., bears N.83°W., 18 lks.
A Fir 20" dia., bears S.38°W., 20 lks.
A Fir 16" dia., bears S.82°E., 13 lks.

Corner found and used by Wm. Byars, GLO survey in July 1882 (DCSO records, Vol. 17 Page 7161)

B.B. Irving, Surveyor -R.L. Irving; N.E. Richardson - Nov. 1930 - C.S. File 37/25

Set a sandstone 4" x 6" x 30". Location identified from O.B.T. scribe marks visible, S.38°W., 20 lks. and O.B.T. N.83°W., 18 lks., marks burned off. Check field notes. Trees formally stood SE and NE checking notes.
16" Fir S.25 3/4°W., 34.0 ft. S4 T31S R5W CC CS BT on bark
16" Fir S.89°E., 27.2 ft. S3 T31S R5W CC CS BT on bark.

Doug. County Surveyors Office - James W. Byron, deputy - Milo Godfrey - C. Putnam - For: C & D Lumber Co. - July 23, 1959 - C.S. File 49168; M 15-33

Found - Orig. 20" now 36" Fir S.38°W., 13.2 ft. previously opened, shows good scribing "S 4 T".
Orig. 6" now 10" Fir snag N.83°W., 11.9 ft. shows old scar, face burned, no scribing found.
No evidence of other original BTs.
Pointed Sandstone at corner, 12"x12"x18" above ground mkd. 6 notches on S. & 4 notches on East.
26" R.Fir bark scribed S3 T31S R5W CC CS BT bears S.85°E., 28.8 ft.
R.Fir bark scribed S4 T31S R5W CC CS BT, S.35°W., 34.0 ft.
Note: these last 2 trees scribed 10 years ago or so.
New BTs -15" R.Fir bears N.87°W., 17.2 ft. scribed S33 T30S R5W CS BT.
36" R.Fir bears S.38°W., 14.5 ft. scribed S4 CS (bark scribed BT)
80 ft. West to creek. 55 ft. North to Creek.

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 378100

PRIMARY CORNER DESCRIPTION N. Sec. Cor. for 3 & 4 only, T31-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM resurvey by Jelley, Roseberry, and Brooks, under Group #'s 320 and 614 - Surveyed June 1966/May 1968 (DCSO records, Vol. 35 Page 14362)

The cor. of secs. 3 & 4 only, on the N. bdy. of the Tp., established by Wright in 1878 as a closing cor. for secs. 3 and 4, adopted by Byars in 1882 as a cor. of maximum control, perpetuated and recorded by B.B. Irving, 1930, monumented with a washed boulder, 36x13x10 ins., firmly set 20" in the ground, mkd. with 4 notches on E and 6 notches on S. edge, from which the remaining bearing trees mkd. by Wright:

A Fir 44" dia., bears S.38°W., 20 lks. dist., with illegible scribe mrks visible on opened blaze.

A Fir stump 12" dia., bears N.83°W., 18 lks. dist., with no marks remaining.

and bearing trees by Irving in 1930

A Fir 27" dia., bears S.89°E., 44 lks. dist., with scribe marks S3 T31S R5W CC CS BT visible on double bark blaze.

A Fir 30" dia., bears S.35°W., 52 lks. dist., with scribe marks S4 T31S R5W CC CS BT visible on double bark blaze.

and a bearing tree mkd. by Byron in 1959

A Fir 15" dia., bears N.87°W., 26 lks. dist., with a healed blaze.

At the Corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T 30 S R 5 W
S 33
S 4 | S 3
T 31 S R 5 W
1967

Deposit the corner stone alongside the iron post.

Fd. Ok. - Raymond Brown - M119-3 - Sept. 1993

Fd. OK Mar. 1995 by R.Brown - M119-60 A-C

Fd. Ok 2/2020 - R. Quimby - C.S. File 65/104-63