

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Pages 7146-47)

Set a post for $\frac{1}{4}$ sec. cor, from which
A B.Oak 8" dia., bears N.27°W., 63 lks.
A Laurel 10" dia., bears N.35°E., 43 lks.

Fd. Post, mkd. & witnessed - by Oscar F. Thiel, under Contract #658 dated May 21, 1896 (DCSO records, Vol. 17 Page 7173)

BLM resurvey by Lynn Roseberry & James Jelley, under Group #662 -Surveyed Oct. 1967/June 1969 (DCSO records, Vol. 38 Pages 15538-39)

Point for the $\frac{1}{4}$ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd:

T 30 S R 5 W
 $\frac{1}{4}$
S 16 | S 15
1969

from which
A Fir 30" dia., bears N.57°E., 39 lks. mkd. $\frac{1}{4}$ S15 BT.
An Oak 6" dia., bears N.45°W., 30 lks. mkd. $\frac{1}{4}$ S16 BT.

Fd. & used BLM resurvey by Wayne L. Rogers, under Group # 1565, surveyed Aug. 1990/July 1991 (DCSO Records Vol. 50 Page(s) 19130)

Fd. Ok by K DeGroot, 7/2006 - M146-42