

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION Cor. Secs 3 & 4 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6424)

Set a post at proper dia. for cor. to secs. 3, 4, 33, & 34, from which,

- A B. Oak, 10" dia., bears S.70°E., 9 lks.
- A B. Oak, 10" dia., bears N.45°E., 22 lks.
- A B. Oak, 8" dia., bears N.40°W., 30 lks.
- A B. Oak, 10" dia., bears S.55°W., 72 lks.

G.L.O. Survey by Oscar F. Thiel, under Contract #658 dated May 21, 1896 (DCSO records Vol. 17 Page 7178)

I set a laurel post, 3' long 4" sq. 24" in the ground for closing cor. of secs. 3 & 4, marked C C T30S R5W on S., S 3 on E., and S 4 on W faces; with 3 grooves on E., and W. faces, from which,

- A laurel, 16" dia., bears S.55°W., 53 lks. dist., marked T30S R5W S4 BT
- A fir, 36" dia., bears S.44°E., 83 lks. dist., marked T30S R5W S3 BT.

As a large amount of dead timber is lying here, I added another BT,

- A laurel, 24" dia., bears N.20°W., 30 lks. dist., marked T30S R5W C C S3 & 4 BT

John Markham, Jr., Engineer - Witnesses: Geo. & Wm Vaughn - April 22, 1951 - For: Hausteader Lbr. Co. - C.S. 40/250A-6

Determined by O.B.T. -

- A Fir 60" dia., bears S.45°E. 56.0' dist. O.B.T.
- A Laurel 26" dia. bears N.10°W., 21.0' dist. O.B.T.; I remark S 34, T29S, R5W, BT.

At corner point set 1"x30" iron pipe, from which

- A Fir 10" dia. bears S.41°W. 8.0' dist. mkd S4, 2880, BT.

B.L.M. Resurvey By Lynn M. Roseberry & James E. Jelley under Group #662. Surveyed Oct. 1967/June 1969 (DCSO records, Vol. 38 Pages 15546)

The original closing cor. of secs. 3 and 4, on the S. bdy. of sec. 34, T. 29 S., R. 5 W., perpetuated and recorded by John H. Markham, Deputy County Surveyor, in 1951, monumented with an iron pipe, 30" long, 1" dia., firmly set, projecting 10" above ground, from which the remains of the original BTs:

- A fir, 50" dia., bears S.45°E., 85 lks. dist., with healed blaze. Record, S.44°E., 83 lks)

(Cont. Next Page)

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION Cor. Secs 3 & 4 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A madrone, 29" dia., bears N.11°W., 33 lks. dist., no and marks visible on decayed blaze. (Rec. N.20°W., 30 lks) a bearing tree mkd. by Markham

A fir, 15" dia., bears S.42°W., 14½ lks dist., with healed blaze.

At the corner point:

Set a iron post, 28 ins. long, 2½ ins. diam., 24" in the ground, with brass cap mkd:

T 29 S R 5 W

S 34

S 4 | S 3

C C

T 30 S R 5 W

1969

Reset iron pipe alongside iron post.

From this cor., the cor., of Secs. 33 & 34, T29S R5w bears N.89°13'W., 6.56 chs. dist.

DCS0-GIS Corner visitation - 3/17/2004 - Typed: 2/8/2011 - C.S. File 67/33-1

Monument - 2.5" BC/IP

Comment - (needs) rehab