

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 434700

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 34, T29-5

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6424)

Set ¼ sec. post at proper distance, from which,
A B. Oak, 10" dia., bears S.33°W., 48 lks.
A B. Oak, 12" dia., bears N.29°W., 63 lks.

John H. Markham, Jr., Engineer - Witnesses: Geo. & Wm Vaughn
- April 22, 1951 - C.S. File 40/259-6

At midpoint on township line set 1"x30" iron pipe, from which
A Fir 6" dia., bears N.32°W., 9.0' dist. mkd ¼ S34 BT.

B.L.M. Resurvey By Lynn M. Roseberry & James E. Jelley under
Group #662. Surveyed Oct. 1967/June 1969. (DCSO records, Vol.
38 Page 15517.)

Point for the ¼ sec. cor. of sec. 34 only, at proportionate
distance; there is no remaining of the original corner. No
permanent monument established.