

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 440440

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 15

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

BLM dependent resurvey by Wayne L. Rogers, Cadastral Surveyor, Under Contract # 1565, surveyed Aug. 1990/ July 1991 (DCSO records Vol. 50 Page(s) 19128-19129)

Point for the center 1/4 sec. cor. of sec. 15, at intersection with the E. and W. center line.
Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T30S R5W
C 1/4 S 15
1991

from which

A fir, 8 ins. diam., bears S. 67° E., 51 lks. dist., mkd.
C 1/4 S15 BT.

A fir, 14 ins. diam., bears N. 13° W., 81 lks. dist., mkd.
C 1/4 S15 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, an iron pipe, 1/2 in. diam., firmly set, projecting 4 ins. above ground, bears S. 18° 14' 00" E., 0.365 chs. dist., established by person(s) unknown. This point is located in a fence extending N. 35° W. and S. 35° E., and is not used in this survey.