

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7147)

Set ¼ sec. post at average distance, from which
A B.Oak 8" dia., bears S.30°E., 20 lks.
A B.Oak 15" dia., bears N.15°W., 60 lks.

Original - Oscar F. Thiel, under Contract #658 dated May 21, 1896 (DCSO records, Vol. 17 Page 7174)

A deligent search failed to show a trace of a corner or any line.
Set a fir post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which
A Laurel 7" dia., bears S.60°E., 6 lks. dist. mkd. ¼ S BT.
A Pine 36" dia., bears N.45°W., 16 lks. dist., mkd. ¼ S BT

John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: W.E. Crawford; R.G. Boyd; J.L. Markham - March 20-25, 1958 - C.S. File 42/349-2

As determined by O.B.T.:
40" Pine bears N.45°W., 10.6 ft., found scribe.
At cor. point set 2" x 2" wood post, from which
24" Laurel bears N.28°E., 34.7 ft. mkd. ¼ S10 BT.
12" Fir bears N.59°E., 30.6 ft. mkd. ¼ S10 BT.
24" Laurel bears S.26°E., 50.0 ft. mkd. ¼ S15 BT.
6" Fir bears S.16½°W., 20.9 ft. mkd. ¼ S15 BT.

Doug. County Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel - July/Aug. 1963 - C.S. File 53/26-6

Found - Stake at corner and all BTs as recorded by Markham except Fir to SE which is now a snag.
Set brass cap at cor. mkd: County Surveyor's $\frac{1}{4} \frac{S 10}{S 15}$ T30S R5W
Office, 1963
No new bearing trees.

BLM resurvey by Lynn Roseberry & James Jelley, under Group #662 -Surveyed Oct. 1967/June 1969 (DCSO records, Vol. 38 Pages 15540-41)

The ¼ sec. cor. perpetuated and recorded by Markham, 1958 and subsequently perpetuated and recorded by Byron 1963, monumented with an iron post, 3/4" dia., firmly set, projecting 14" above ground, with brass cap properly mkd.
(Cont. Next Page)

