

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Oscar F. Thiel, under Contract #658 dated May 21, 1896 (DCSO records, Vol. 17 Page 7177)

Set a Cedar post 5" sq., 3 ft. long, 24" in the ground for ¼ sec. cor., mkd. ¼ S on N. face, from which:
A Fir 12" dia., bears N.54°E., 24 lks. dist. mkd. ¼ S BT.
A Vine maple 5" dia., bears S.44½°E., 20 lks. mkd. ¼ S BT.

BLM resurvey by Lynn Roseberry & James Jelley, under Group #662 -Surveyed Oct. 1967/June 1969 (DCSO rec Vol 38 Pg 15544)

Point for ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd: T 30 S R 5 W
¼ $\frac{S 3}{S 10}$
1969

from which
A Fir 10" dia., bears N.62°E., 161 lks. mkd. ¼ S3 BT.
A Maple 20", bears N.22°W., 175 lks. mkd. ¼ S3 BT.

Fd. OK, November 1986, H. Johnstone, M 103-1

BLM resurvey by Wayne L. Rogers, under Group # 1565, surveyed Aug. 1990/July 1991 (DCSO Records Vol. 50 Page(s) 19112-13)

From the ¼ sec. cor. of secs. 3 and 10, determined at record bearing & distance from the BTs mkd. by Roseberry and Jelley:
A fir, 19" dia. bears N.62°E., 161 lks. with healed blaze.
A maple, 28" dia., bears N.22°W., 175 lks. with scribe marks 1/4 S3 BT visible on open blaze.

At the corner point
Set an stainless steel post, 2½" dia., 28" long, 26" in the ground with brass cap mkd. T30S R5W
1/4 $\frac{S 3}{S 10}$
1990

from which a new bearing tree
A fir, 10" dia., bears S.27°W., 131 lks. mkd. ¼ S10 BT.
Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

DCSO-GIS Corner visitation - 3/8/2005 - Typed: 2/8/2011 - C.S. File 67/33-1

Monument - 3" BC Comment - OK
_____ cont. next pg

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2812, surveyed Sept. 2015 - (DCSO records Vol. 58 Page 23490 & Plat T30-5 2017-1)

The ¼ sec. cor. of secs. 3 & 10, monumented with an iron post, 2½" dia., firmly set, projecting 1" above ground, with brass cap (properly) mkd.

from which the bearing trees mkd. by Roseberry and Jelley in 1967-69, reported by Rogers in 1990-91

A fir, 29" dia., bears N.62¾°E., 106.3 ft., with a healed double blaze. (Record, N.62°E.)

A maple, 29" dia., bears N.21°W., 115.5 ft., with a hollowed blaze. (Record, N.22°W.)

and the bearing tree mkd. by Rogers in 1990-91

A fir, 20" dia., bears S.28½°W., 86.5 ft., with a healed blaze. (Record, S.27°W.)

NAD 1983 (2011)

Latitude 42°59'00.62"N.

Longitude 123°16'32.11"W.