

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 440640

PRIMARY CORNER DESCRIPTION Center 1/4 Sec. 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Wayne L. Rogers, Cadastral Surveyor, Under Contract # 1565, surveyed Aug. 1990/ July 1991 (DCSO records Vol. 50 Page(s) 19113-19114)

-----  
Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T30S R5W  
C 1/4  
S 3  
1990

from which

A fir, 11 ins. diam., bears S. 63° E., 24½ lks. dist., mkd. C 1/4 S3 BT.

A maple, 10 ins. diam., bears S. 20½° W., 48 lks. dist., mkd. C 1/4 S3 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

DCSO-GIS Corner visitation - 3/14/2005 - Typed: 2/8/2011 - C.S. File 67/33-1

-----  
Monument - 3" BC                      Comment - (needs) rehab