

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 440700

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 3 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6424)

Set ¼ sec. post at proper distance, from which,
A B. Oak, 10" dia., bears S.33°W., 48 lks.
A B. Oak, 12" dia., bears N.29°W., 63 lks.

John H. Markham, Jr., Engineer - Witnesses: Geo. & Wm. Vaughn - April 22, 1951 - C.S. File 40/259-6

At midpoint on township line set 1"x30" iron pipe, from which
A Maple 20" dia., bears S.83°E., 51.0' dist. mkd ¼ S 3 BT.

B.L.M. Resurvey By Lynn M. Roseberry & James E. Jelley, under Group #662. Surveyed Oct. 1967/June 1969. (DSCO records Vol. 38 Page 15547)

The point for the ¼ sec. cor. of sec. 3 only, T. 30 S., R. 5 W., is at midpoint on the N. bdy. of sec. 3.
Set an iron post, 28" long, 2½" diam., 24" in the ground, with brass cap mkd:

 ¼ S 3
 T 30 S R 5 W
 1969

from which
A fir, 32" dia., bears S.6°E., 91 lks. dist., mkd S3 BT.
A fir, 11" dia., bears S.7½°W., 88½ lks. dist., mkd S3 BT.

Fd. & used by BLM resurvey by Wayne L. Rogers, under Group # 1565, surveyed Aug. 1990/July 1991 (DCSO Records Vol. 50 Page(s) 19114)

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2795, surveyed July/Aug. 2015- (DCSO records Vol. 59 Page 23568)

The ¼ sec. cor. of sec. 3 only, T. 30 S., R. 5 W., monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd.
from which the BTs mkd. by Roseberry and Jelley in 1967-69
A fir, 42" dia., bears S.6°E., 60.1 ft., with a healed blaze.
A fir, 19" dia., bears S.7½°W., 58.4 ft., with a healed blaze.