

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 446100

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. Sec. 3 only, T31-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 456 dated July 28, 1882 (DCSO rec. Vol. 17 Pages 7161-62)

Set a stone 24 x 6 x 6 ins. 12" in the ground for the 1/4 sec. cor. mkd. ¼ on the N. side and from which

A Fir 22" dia., bears N.5°E., 100 lks. dist. mkd.

¼ S BT.

A Laurel 12" dia., bears S.48°W., 21 lks. dist. mkd.

¼ S BT.

BLM resurvey by Jelley, Roseberry, and Brooks, under Group #'s 320 and 614 - Surveyed June 1966/May 1968 (DCSO records, Vol. 35 Page 14361)

The ¼ sec. cor. of sec. 3 only, on the N. bdy. of the Tp., established by Byars in 1882, monumented with the orig. basalt stone 24 x 6 x 6 ins., firmly set 8" in the ground, mkd. ¼ on N. face, from which the original bearing trees:

A Fir 45" dia., bears N.5°E., 102 lks. dist., with illegible scribe marks visible on a bark blaze. (Rec. 100 lks.)

A Madrone 26" dia., bears S.46½°W., 21 lks. dist., with a healed blaze. (Rec. S.48°W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock, supported in a mound of stone, 5 ft. base, to top, with brass cap mkd:

¼ S 3
T 31 S R 5 W
1967

from which a new bearing tree

A Fir 22" dia., bears S.55½°E., 43½ lks. dist., mkd.

¼ S3 BT.

Deposit the corner stone alongside the iron post.

Fd. OK, Raymond Brown, Sept. 1993, M119-3

Fd. OK, Raymond Brown, Mar. 1995 - M119-60 A-C

Found Ok Aug. 2005 by N. Hibbs - M146-25