

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 and 35 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7133)

Set a post at proper distance, corner of secs. 2, 3, 34 and 35, from which

- A R.Fir 20" dia., bears S.33°W., 38 lks. dist.
- A R.Fir 10" dia., bears S.27°E., 47 lks. dist.
- A Laurel 6" dia., bears N.18°W., 64 lks. dist.
- A Laurel 12" dia., bears N.49°E., 32 lks. dist.

BLM resurvey by Jelley, Roseberry, and Brooks, under Group #'s 320 and 614 - Surveyed June 1966/May 1968 (DCSO records, Vol. 35 Pages 14360-61)

Point for the cor. of secs. 34 and 35 only, on the S. bdy. of T30S R5W established by extending the line bet. secs. 34 and 35 through the orig. 1854 Ford cor. of secs. 2, 3, 34 and 35, to an intersection with the 1882 Byars township line.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T 30 S R 5 W
S 34 | S 35
S 3
T 31 S R 5 W
1967

from which

- A Fir 20" dia., bears N.20¼°E., 23 lks mkd T30S R5W S35 BT
 - A Fir 18" dia., bears N.57½°W., 37 lks mkd T30S R5W S34 BT
- From this point the original 1854 Ford cor. of secs. 2, 3, 34 and 35, bears N.0°57'E., 5.58 chs., monumented with an iron pipe 1" dia., protruding 6" above ground firmly set, witnessed as described in the 1967 resurvey.

(See BLM survey notes in Vol. 35 Page 14396 for "off line closing cor." for the old 1854 Ford corner)

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - Feb. 20, 2013 - C.S. File 67/38-20

Found - Orig. monument established n 1967; a 3¼" dia., brass cap (properly mkd.) on a 2½" O.D. IP is firmly and plumbly set protruding 6" above ground.

A fir 20" dia., now a 20"x1½" ft tall fir stump, half of stump is gone stump is rotted and remnant of blaze is burned and shows no scribing. This stump bears N.20¼°E. 15.2 ft (as per rec) 1967

A fir 18" dia., now a 21" dia., D.Fir with no blazes evident (bark is burned) bears N.57½°W., 25.3 ft. (rec. N.57½°W., 24.4 ft.) 1967

continued next page

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 and 35 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New - A 12" dia. Live Oak scribed "T30S R5W S35 CS" "BT"
on a double blaze; bears N.30¼°E., 53.6 ft.
A 26" dia., D.Fir scribed "T31S R5W S3 CS" "BT" on
a double blaze; bears S.8¾°W., 47.9 ft.
A 9" dia., Madrone scribed "X CS" "BT" on a double
blaze; bears S.31½°W., 28.8 ft.
Note - Monument is on steep ESE slope approx. 200 ft. above
I-5 is an open forest of fir, Live Oak, &
madrone.
Compass decl. 15½°E.

Ron Quimby - Crew: N. Fromdahl & L. Heddens - 3/2020 - C.S.
File 65/106-5

Found - BLM brass cap (properly mkd)
21" Fir stump N.57°W., 25.3 (burnt)
12" Live Oak N.30°E., 53.6 ft. good scar.
26" D.Fir S.9°W., 47.9 ft. good scar.
9" madrone S.31°W., 28.8 ft. good scar.
Brass cap sec cor. 2 & 3 only, east 97.8 ft.
New - 5' alum post 15.0 west
5' alum post 15.0 north
Note - Compass decl. 15½°E.