

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7139)

Set ¼ sec. post, from which
A B.Oak 10" dia., bears S.37°E., 110 lks. dist.
A Laurel 6" dia., bears N.68°W., 71 lks. dist.

BLM resurvey by Lynn Roseberry, under Group #'s 350 and 614 -Surveyed Sept. 1967 (DCSO records, Vol. 35 Page 14395)

Point for the ¼ sec.cor.of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

¼
S 34 S 35
1967

from which
A Maple 7" dia., bears N.12¼°E., 9 lks. mkd. ¼ S35 BT.
A Maple 13" dia., bears N.80½°W., 204 lks. mkd. S34 BT.

Found OK by R.Brown Mar. 1995 - M119-60 A-C