

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7140)

-
- Set a post cor. of secs. 26, 27, 34 & 35, from which
- A W.Oak 10" dia., bears S.80°E., 40 lks.
 - A W.Oak 12" dia., bears S.10°W., 50 lks.
 - A B.Oak 8" dia., bears N.20°E., 62 lks.
 - A B.Oak 15" dia., bears N.15°W., 59 lks.

G.G. Stewart, set in presence of Chas. Leiser; J.G. Baker; M. Jones - Jan. 4, 1922 - C.S. file 7/2-00B, Vol. 3 Pg. 107 and "old" Cor. Bk. Pg.147

-
- Reset from two old BTs. Set Iron Pipe, from which
- 18" B.Oak S.80°E., 40 lks.
 - 12" B.Oak S.12°W., 33.0 ft.
 - 24" B.Oak North, 35.2 ft.
 - 24" Fir bears N.89°E., 68.5 ft.

Geo. Wenderoth - 1953-54 - C.S. File 41/18

-
- 1/2 inch I. Pipe at corner point. From which
- 24" Fir N.87°40'E., 68.5 ft.
 - 14" W.oak S.60°30'W., 63.0 ft.
 - 36" B.Oak S.78°30'E., 33.3 ft.
 - 24" B.Oak N.78°45'W., 54.6 ft.

BLM resurvey by Lynn Roseberry, under Group #'s 350 and 614 -Surveyed Sept. 1967 (DCSO records, Vol. 35 Page 14394)

The cor. perpetuated and recorded by G.G. Stewart, 1922, monumented with an I.P. 1/2" dia., protruding 5" above ground, firmly set, from which the remaining original bearing trees:

- A root hole bears S.80°E., 40 lks. dist., alongside of which is an uprooted and rotted Oak, 18" dia., with illegible scribe marks visible on opened and rotted blaze.
 - A root hole bears S.10°W., 50 lks. dist., alongside of which is an uprooted and rooted Oak, 14" dia., with scribe marks S34 BT visible on opened and rotted blaze.
- and bearing trees mkd. by Stewart in 1922
- A root hole bears North, 55½ lks. dist., alongside of which is an uprooted and rotted Oak, 24" dia., with no marks visible.
 - A Fir 32" dia., bears N.88½°E., 106 lks. dist., with a healed blaze.

(Cont. Next Page)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and bearing trees mkd. by Wenderoth in 1963
 A B.Oak 31" dia., bears S.83°E., 50½ lks. dist., with scribe marks S35 CS BT visible on open blaze.
 A W.Oak 14" dia., bears S.58½°W., 94 lks. dist. with scribe marks 3 CS visible on open blaze.
 A B.Oak 20" dia., bears N.80 ¾°W., 83 lks. dist., with scribe marks S27 CS BT visible on open blaze.
 At the corner point
 Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground directly over the iron pipe, with brass cap mkd:
 T 30 S R 5 W
 S 27 | S 26
 S 34 | S 35
 1967

Fd. OK, July 1983, Wm. Ruppert, M 94-66
 Fd. OK March 1995 by R.Brown - M119-60 A-C

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch
 - Jan. 17, 2013 - C.S. File 67/38-2

 Found - A 3¼" dia., brass cap (properly mkd) on a 2½" ID iron pipe, firmly & plumbly set, protruding 6" dia., above ground.
 1953-54 iron pipe monument set under BC monument (not looked for)
 Possible evidence of 2 orig. BTs:
 A W.Oak 10" dia., an 18" dia., W.Oak with a possible rotted blaze (we do not open further) is fd, out of position, but near SE quadrant OBT bearing & dist. No root-hole remains.
 A W.Oak, 12" dia., now a fallen (on face) and rotted 18" dia., W.Oak with no blaze evident; the root of which bears S.10°W., 33.0 ft. (as per rec)
 A 24" fir now a 40" dia., D.Fir stump, 4 ft. tall, but showing no blaze evidence (we do not open); bears S.89°E., 68.5 ft. (N.89°E., 68.5 ft.) 1922
 A 36" B.Oak, now a fallen & very rotted out of position with no remaining blaze evidence; the possible root-hole of which bears S.80°E., 33.3 ft. (rec. S.78½°E., 33.3 ft.) 1953-54
 A 24" Oak, now a clear well defined root-hole (no identifiable evidence of tree fd.) bears N.78¾°W., 54.6 ft. (as per rec) 1953-54
 A 14" W.Oak now a 16" dia., W.Oak with a fully healed double blaze; bears S.60½°W., 63.0 ft. (as per orig. rec.)

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New - A 29" dia., D.Fir scribed "T30S R5W S26 CS" "BT" on a double blaze; bears N.49½°E., 7.9 ft.
A 22" dia., Madrone scribed "T30S R5W S35 CS" "BT" on a double blaze; bears S.18¼°E., 48.0 ft.
A 26" dia., B.Oak scribed "T30S R5W S27 CS" "BT" on a double blaze; bears N.72½°W., 79.9 ft.
Compass decl. 15½°E.