

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7140)

Set ¼ sec. post, from which
A W.Oak 10" dia., bears S.80°E., 40 lks.
A B.Oak 8" dia., bears N.20°W., 62 lks.

George Wenderoth - 1953-54 - C.S. File 41/18

Corner set 1/2 way between section corners.
3/4" iron pipe at corner.
From which
20" Madrone N.50°43'W., 42.5 ft.
12" Fir N.6°16'E., 30.0 ft.

Fd. I.P. & BT's, R. Brown, 10/93 - M 119-4

Doug. Co. Surveyors Office - Randall Smith & Stephen Flaue
-Oct. 28, 93 - C.S. file 64/47-11

Monuments Fd.
3/4" I.D. broken iron pipe, portion of pipe remaining in ground found 4" below surface. (1953 Wenderoth).

Accessories Fd.
12" now 21" dia. D.Fir with a fully healed double blaze bears N.4°E., 30' (Rec. N.6¼°E., 30') 1953 Wenderoth.
20" now 24" dia. 3' high burnt madrone snag no scribing visible on a partially healed blaze, bears N.50 3/4°W., 42.5' (agrees with rec.) 1953 Wenderoth.

Monuments Set
1 3/8" O.D. x 32" long iron pipe with a 2 3/8" dia. DCSO brass cap is set at referenced position of 3/4" I.D. iron pipe, BC/IP protrudes 5" above ground.
3/4" I.D. I.P. had an overall length of 19" IP. pieces are set along north edge of DCSO BC/IP, protruding 3" above ground.

New Accessories
3" dia., cedar, double blazed and scribed "X BT", bears S.53°E., 15.4'.
7" dia., madrone bark scribed "¼S27 CS BT", bears N.85½°W., 8.4'.
11" dia., madrone, double blazed and scribed "¼S27 CS BT", bears S.24°W., 16.5'.