

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7143)

Set ¼ sec. post, from which
A B.Oak 15" dia., bears N.75°E., 32 lks.
A Laurel 18" dia., bears S.70°W., 87 lks.

BLM resurvey by Roseberry and Jelley, under Group # 662 - Surveyed Oct. 1967/June 1969 (DCSO records, Vol. 38 Pg 15526)

Point for the ¼ sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T 30 S R 5 W
 ¼
 S 15 | S 14
 1969

from which

A Cedar 12" dia., bears N.51½°E., 39 lks., mkd. ¼ S14 BT.
A Fir 13" dia., bears S.60½°W., 32 lks., mkd. ¼ S15 BT.

Fd. and used by BLM resurvey by Wayne L. Rogers, under Group # 1565, surveyed Aug. 1990/July 1991 (DCSO Records Vol. 50 Page(s) 19110)

DCSO-GIS Corner visitation - 12/16/2004 - Typed: 2/8/2011 - C.S. File 67/33-1

Monument - 2½" IP/BC Comment - (needs) rehab

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - 2/11/2013 - C.S. File 67/38-17

Found - A 3¾" dia., brass cap (properly mkd) on a 2" I.D. iron pipe is firmly and plumbly set, protruding 6" above ground.

No OBTs fd, we open & inspect large madrones in vicinity but find no BT evidence. No large B.Oaks remain.

A cedar 12" dia., now a 19" dia., I.Cedar with a fully healed low single blaze; bears N.49½°E., 23.8 ft. (Rec. N.51½°E., 25.7 ft.) 1969

A fir 13" dia., now 24" D.Fir with a fully healed double blaze; bears S.58½°W., 21.1 ft. (rec. S.60½°W., 21.1 ft.) 1969

continued next page

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New - An 18" dia., D.Fir scribed "¼ S14 CS" "BT" on a double blaze; bears S.46½°E., 36.6 ft. (nearer fir in this quadrant has unascrivable base)
A 16" dia., madrone scribed "¼ S15 CS" "BT" on a double blaze; bears N.63½°W 21.4 ft.

Note - Monument is on gentle east slope of a broad ridge in a mature woods with fir, madrone, cedar & oak, BLM road #30-5-14.0 is 120 ft west from corner. Compass decl. 15½°E.

Fd. as per record 3/2024 by D Edwards M183-42