

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Oscar F. Thiel, under Contract #658 dated May 21, 1896 (DCSO records, Vol. 17 Page 7170)

Set a basalt stone 14x9x6 ins. 10" in the ground, cor. of secs. 2, 3, 10 and 11, 800 ft. above creek, mkd. with 5 notches on S., and 2 notches on E. edges, from which
A B.Oak 36" dia., bears N.49 3/4°E., 44 lks. mkd. T30S R5W S2 BT.
A B.Oak 36" dia., bears S.4 3/4°E., 51 lks. dist., mkd. T30S R5W S11 BT.
A Pine 9" dia., bears S.38 3/4°W., 125 lks. dist., mkd. T30S R5W S10 BT.
A B.Oak 30" dia., bears N.61 1/4°W., 111 lks. dist., mkd. T30S R5W S3 BT.

Burton W. Holt, L.S. #418 - V.E. Essary; J.H. Markham, Jr. - July 22, 1958 - C.S. File 42/377-1

As determined by old BTs:
26" B.Oak N.65°W., 75 ft.
26" P.Pine S.37°W., 82 ft.
22" B.Oak N.46°E., 31 ft.
At corner found original stone and set 1" x 30" I.Pipe, from which:
5" Madrone bears N.51°E., 20.0 ft. mkd. S2 BT.
6" Madrone bears N.17°E., 32.0 ft. mkd. S2 X BT.
9" Madrone bears N.19°W., 26.8 ft. mkd. S3 BT.
10" Madrone bears S.78°W., 65.0 ft. mkd. S10 BT R5W
7" Madrone bears S.26°E., 13.0 ft. mkd. S11 T30S BT.
Old fence bears S.70°E., and N.70°W. through corner.
Corner lies on nose of East ridge.

BLM resurvey by Lynn Roseberry & James Jelley, under Group #662 - Surveyed Oct. 1967/June 1969 (DCSO records, Vol. 38 Pages 15530-31)

The Sec. cor. perpetuated and recorded by Holt, 1958, monumented with an iron pipe 1" dia., firmly set, projecting 8" above ground, with a washed boulder alongside, 14 x 6 x 5 ins., firmly set 8" in the ground, mkd. with S2 on NE., S11 on SE., S10 on SW., and S3 on NW. faces, from which the remains of the original bearing trees:
A B.Oak 25" dia., bears N.50 1/4°E., 47 lks., no marks visible on opened decayed blaze. (Rec. N.49 3/4°E., 44 lks.)
A Pine 28" dia., bears S.39 3/4°W., 123 lks. dist., with scribe marks 10 visible on opened blaze. (Rec. S.38 3/4°W., 125 lks.) (Cont. Next Page)

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. 2, 3, 10 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

- A B.Oak 30" dia., bears N.60 3/4°W., 108 lks. dist., with scribe marks S2 visible on opened blaze. (Rec. N.61 1/4°W., 111 lks.)
and bearing trees mkd. by Holt
- A Madrone 8" dia., bears N.21 1/4°E., 49 lks. dist., with scribe marks S2 X BT visible on partially healed double blaze.
- A Madrone 5" dia., bears N.54 3/4°E., 39 1/2 lks. dist., with scribe marks S2 BT visible on partially healed double blaze.
- A Madrone 8" dia., bears S.21 3/4°E., 20 lks. dist., with scribe marks S11 T30S BT visible on partially healed double blaze.
- A Madrone 12" dia., bears S.79 1/2°W., 99 lks. with scribe marks S10 BT R5W visible on partially healed double blaze.
- A Madrone 9" dia., bears N.10 1/4°W., 41 lks. dist., with scribe marks S3 BT visible on partially healed double blaze.

At the Corner Point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd:

T 30 S R 5 W
S 3 | S 2
S 10 | S 11
1969

Deposit washed boulder alongside iron post.