

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 and 35

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7140)

Set ¼ sec. post at average dist., from which
A Laurel 4" dia., bears N.85°W., 11 lks.
A Laurel 4" dia., bears S.35°W., 9 lks.

B.B. Irving - For: Schaeffer - July 29, 1930 - C.S. File 37/37 and "old" Cor. Bk. Pg. 183

Drove Ford axle at mid point between section corners.
Marked:
8" Fir N.10°E., 7 lks. blazed & scribed ¼ S26 CS BT.
10" Fir S.35°W., 6 lks. blazed & scribed ¼ S35 CS BT.

BLM resurvey by Lynn Roseberry, under Group #'s 350 and 614 -Surveyed Sept. 1967 (DCSO records, Vol. 35 Page 14393)

The ¼ sec. cor. of secs. 26 and 35, reestablished and recorded at proportionate distance by B.B. Irving, in 1923; there is no remaining evidence of the orig. cor., so this point is accepted as the best available evidence of the cor. location. The corner is monumented with an iron bar, 1½ ins. dia., protruding 10" above ground, firmly set, from which the bearing trees mkd. by Irving in 1923:

A root hole, bears N.10°E., 7 lks. dist., alongside of which is an uprooted Fir, 12" dia., with a healed blaze.

A sawed Fir stump 17" dia., bears S.35°W., 8 lks. dist. with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd: T 30 S R 5 W

¼ $\frac{S\ 26}{S\ 35}$
1967

from which new bearing trees

A Fir 12" dia., bears N.22½°E., 85 lks. mkd. ¼ S26 BT.

A Madrone 13", bears S.50°W., 57 lks. mkd. ¼ S35 BT.

Fd. Brass cap & BT's Oct. 1993 - Raymond Brown, M 119-4