

TOWNSHIP 30 RANGE 5 POINT IDENTIFIER # 540540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor Sec 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician, under Group #1906, surveyed June/Aug. 1999. (DCS0 rec. Vol. 53 page(s) 20516)

-----  
Point for the center ¼ sec. cor. of sec. 11, at intersection with the E. & W. centerline.

Set a stainless steel post, 28" long, 2½" diam., 24" in the ground, with brass cap mkd. T 30 S R 5 W  
C 1/4 S 11  
1999

from which

A fir, 14" dia., bears S.89½°E., 9.1 ft., mkd. C¼ S11 BT.

A fir, 7" dia., bears S.10°E., 11.9 ft., mkd. X BT.

Each new bearing tree has a 2½" X ¼" magnetic nail (Mag Nail) driven at the base on right side-center, unless otherwise described in the corner description.

Deposit a magnet in a white plastic case at base of stainless steel post.

David Edwards - For: Briggs Management LLC & Seneca Jones Timber Co. 7/2023 - C.S. file 65/112-001

-----  
Found - BLM brass cap  
15" dia., Fir w/healed blaze bears S.89½°E., 9.1'  
9" dia., Fir snag w/healed blaze bears S.10°E. 11.9'  
New - 12" dia., Fir scribed "C ¼ S11 BT" bears N.15°E.,  
27.7'  
5.5 ft. steel posts are set 2 ft S.89°E., & 2 ft. north.