

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Original - Oscar F. Thiel, under Contract #658 dated May 21, 1896 (DCSO records, Vol. 17 Page 7171)

Set a Fir post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which
A W.Oak 12" dia., bears N.74°W., 17 lks. dist., mkd. ¼ S BT.
A W.oak 14" dia., bears S.25½°W., 23 lks. dist., mkd. ¼ S BT.

John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: W.E. Crawford; R.G. Boyd; J.L. Markham - March 20-25, 1958 - C.S. File 42/349-6

As determined by O.B.T.:
15" W.Oak stump bears N.74°W., 11.2 ft. found scribe.
14" W.Oak stump bears S.25°W., 15.2 ft.
At corner point set 1" x 30" Iron pipe, from which
11" Cedar bears S.78°30'W., 53.1 ft. mkd. ¼ S11 T30S BT
10" Fir bears N.80°30'W., 46.7 ft. mkd. ¼ S2 BT.
10" Fir bears N.21°W., 61.0 ft. mkd. ¼ S2 BT.
Top of ridge bears East, 200 ft. Road bears North, 31.0 ft.

Doug. County Surveyors Office - James W. Byron, Deputy - Mike Darby - Sept. 1963 - C.S. File 53/26-7

Found - 1" I.Pipe.
11" now 13" Cedar S.78½°W., 53.1 ft. shows scribing.
Now 12" Fir snag N.80½°W., 46.7 ft. shows scribing.
New BT - 17" R.Fir bears N.82°W., 60.2 ft. scribed ¼ S2 CS BT

BLM resurvey by Lynn Roseberry & James Jelley, under Group #662 -Surveyed Oct. 1967/June 1969 (DCSO records, Vol. 38 Pages 15531-32)

The ¼ sec. cor. perpetuated and recorded by Markham, 1958, from original evidence no longer in existence, and subsequently perpetuated and recorded by Byron in 1963, monumented with an iron pipe 1" dia., firmly set, projecting 10" above ground, from which the remains of bearing trees mkd. by Markham:
A Fir stump 10" dia., bears N.21°W., 92½ lks. dist., with scribe marks ¼ S2 BT visible on partially healed double blaze.

(Cont. Next Page)

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir snag 12" dia., bears N.80½°W., 71 lks. dist., with scribe marks ¼ S2 BT visible on partially healed double blaze.

A Cedar 28" dia., bears S.78½°W., 80½ lks. dist., with scribe marks ¼ S11 T30S R5W BT visible on partially healed double blaze.

and a bearing tree mkd. by Byron:

A Fir 17" dia., bears N.82°W., 91½ lks. dist., with illegible scribe marks visible on partially healed blaze.

At the Corner Point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd:

T 30 S R 5 W

¼ $\frac{S\ 2}{S\ 11}$

1969

Fd. OK by W. Rogers, April 2000 - M134-52

Fd. & used BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician, under Group #1906, surveyed June/Aug. 1999. (DCS0 rec. Vol. 53 page(s) 20514-5)