

PRIMARY CORNER DESCRIPTION Center 1/4 cor. Sec. 2

Alias	Description

Wayne Rogers - For: Webb Briggs - April 2000 - M 134-52  
-----  
Set - 5/8"x30" iron rod w/cap mkd: "I.E. ENGINEERING" from which:  
A Cedar, 12" dia., bears N.82°E., 45.8 ft., scribed: C¼ S2 BT.  
A Cedar, 8" dia. bears S.57½°E., 44.1 ft. scribed: X BT  
A Cedar, 6" dia., bears S.32°W., 3.0 ft., scribed: C¼ S2 BT.  
A Fir, 15" dia., bears N.3½°W., 17.5 ft., scribed: C¼ S2 BT.

Douglas Co. Surveyor's Office - Crew: Stephen J Flause & Jeffery Lorsung - 9/10/2018 - C.S. File 67/45-19  
-----  
Found - A 5/8" iron rod by H. Johnstone in 1980, firmly set, projecting 12" above the ground with a 2" aluminum cap (properly) mkd.  
A rotted 8" (dia. x 8" tall D.Fir stump bears, N.79°E., 22.9 ft. (Rec. 23.6 ft.)  
New - A 11" D.Fir bears N.4°E., 6.6 ft. scribed "C ¼ S2" "CSBT".  
A 12" D.Fir bears, S.22½°E., 5.2 ft. scribed "C ¼ S2 CS" "BT".  
A 10" D.Fir bears, S.84°W., 15.5 ft. scribed "C ¼ S2 "CSBT".  
A 14" D.Fir bears, N.38½°W., 22.0 ft. scribed "C ¼ S2", "CSBT".

LOCATION & COMMENTS -  
All BTs have BT tags attached. All new BTs have double blazed faces with bearings measured to the center of the tree at the root crown and distances measured to the side and center of the root crown.  
K-tag placed East approximately 50 ft. along the unnamed BLM ridge road.

COMPASS DECLINATION: 15°E.  
GEODETIC COORDINATES  
LATITUDE: 42°59'49.625" N LONGITUDE: 123°01'54.087" W  
DATUM: NAD 83, Epoch 2010.00  
SOURCE: Trimble GeoXT 6000