

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 541100

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. Sec. 2 only, T31-5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 456 dated July 28, 1882 (DCSO rec. Vol. 17 Pages 7162-63)

-----  
Set a Laurel post 3 ft. long 3" sq. 18" in the ground for the 1/4 sec. cor. mkd. 1/4 S on the N. side and from which  
A Laurel 14" dia., bears N.15°W., 25 lks. dist. mkd.  
¼ S BT.  
A Laurel 12" dia., bears S.10°E., 30 lks. dist., mkd.  
¼ S BT.

Doug. County Surveyors Office - James W. Byron, deputy - Mike Darby; Jim Halterman - Nov/Dec. 1963 - C.S. File 53/26-43

-----  
Found - Orig. 12" now 20" Laurel S.10°E., 21.0 ft.  
Orig. now 20" Laurel stump N.15°W., 17.8 ft.  
We open SE BT and find good scribing "T".  
New BTs -13" Cedar bears S.38°E., 28.0 ft. scribed ¼ S2 CSBT.  
22" Laurel bears N.25°W., 20.0 ft scribed ¼ S35 CSBT  
Corner is on West slope, 100.0 ft. East of small stream.

BLM resurvey by Jelley, Roseberry, and Brooks, under Group #'s 320 and 614 - Surveyed June 1966/May 1968 (DCSO records, Vol. 35 Page 14358)

-----  
The 1/4 Cor. on the N. bdy. of The Tp. established by Byars in 1882, perpetuated and recorded by Byron in 1963, monumented with an iron rod ½" dia., protruding 6" above ground, firmly set, from which the original bearing trees:  
A Madrone stump 20" dia., bears N.15°W., 28 lks. dist., with no marks remaining. (Rec., 25 lks.)  
A Madrone 20" dia., bears S.10°E., 32½ lks. dist., with scribe mark T visible on opened blaze. (Rec. 30 lks.)  
and bearing trees mkd. by Byron in 1963  
A Madrone 23" dia., bears N.27½°W., 32 lks. dist., with scribe marks ¼ S325 CS BT visible on open blaze.  
A Cedar 15" dia., bears S.40°E., 43 lks. dist., with scribe marks ¼ S2 CS BT visible on open blaze.

At the corner point  
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd:

-----  
¼ S 2  
T 31 S R 5 W  
1967

from which a new bearing tree  
A Fir 18" dia., bears S.46°W., 105½ lks. dist.,  
mkd. ¼ S2 BT.

CONT.

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 541100

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. Sec. 2 only, T31-5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Cor. Fd. OK, BLM resurvey by Berry and Akin, 1972-73 under Group #800 (DCSO records, Vol. 38 Page 15654)

BLM dependent resurvey by Markell G Hamm, Cadastral Surveyors, under Group #2927, surveyed June/Sept. 2017 - (DCSO records Vol. 59 Page(s) 23726)

-----  
The ¼ sec. cor. of sec. 2 only, on the N. bdy. of the Tp., reported by Berry and Akin in 1972-73, monumented with an iron post, 2½" dia., firmly set, projecting 5" above ground, with a brass cap (properly) mkd.

from which the bearing trees reported by Berry and Akin

A cedar, 32" dia., bears S.40°E., 28.4 ft., with a healed blaze.

A madrone, 19" dia., bears S.10°E., 21.5 ft., with no marks visible on partially healed and decayed blaze.

This tree is not healthy. (Original)

A fir, 30" dia., bears S.46°W., 69.6 ft., with a healed blaze.

A madrone, 24" dia., bears N.27½°W., 21.1 ft., with a healed blaze.

Corner is located in sparse poison oak, fir, madrone, and cedar.