

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 574700

PRIMARY CORNER DESCRIPTION Sec Cor 35 & 36 only, T29-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6423)

Set a post for cor. to secs. 1, 2, 35, & 36, from which,
A Yellow Pine, 20" dia., bears S.30°E., 100 lks.
A B. Oak, 10" dia., bears N.26°E., 42 lks.
A Laurel, 20" dia., bears N.31°W., 100 lks.
A B. Oak, 18" dia., bears S.27°W., 80 lks.

G.L.O. Survey by Oscar F. Thiel, under Contract #658 dated May 21, 1896. (DCSO records Vol. 17 Page 7183)

I set a basalt stone 7x8x9, 6" in the ground for cor. of secs. 35 & 36. T. 29 S., R. 5 W., marked with 1 groove on the E., and 5 grooves on the W. faces, and raised a mound of stone, 2' base, 1½' high N. of cor. No trees within limits.

B.L.M. Resurvey by Irving Zirpel, Jr. under Group #355. Surveyed July 1957/Sept. 1957. (DCSO records Vol. 28 Page 12113)

Set an iron post, 30" long, 2" dia., 28" in the ground, with brass cap mkd:
T29S R5W
S 35 | S 36
T30S R5W
S 2
1957

from which

A Fir, 15" dia., bears N.46°E. 75 lks. dist., mkd T29S R5W S36 BT.
A Fir, 13" dia., bears N.87½°W., 42 lks. dist., mkd T29S R5W S35 BT.

Doug. County Surveyors Office - James Byron, Deputy - M. Darby - Wm. Stoffel - June 1963 - C.S. File 49/64-81

Found - Brass Cap at Corner
13" Fir, N.87°W., 27.7', shows scribing.
15" Fir, N.46°E., 49.5', now down.
New BT - 12" Fir, N.86°E., 29.3', scribed T29S R5W S36 CS BT.

B.L.M. Resurveyed By Lynn M. Roseberry, & James E. Jelley under Group #662. Surveyed Oct. 1967/June 1969. (DCSO records, Vol. 38 Page 15514).

CORNER REPORT ONLY

(Cont. Next Page)

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 574700

PRIMARY CORNER DESCRIPTION Sec Cor 35 & 36 only, T29-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

The cor. of secs. 35 & 36 only, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap mkd:

T 29 S R 5 W
S 35 | S 36
T 30 S R 5 W
S 2
1957

from which the remains of bearing trees mkd. by Zirpel
A root hole, bears N.46°E., 75 lks. dist., with a down fir alongside, 15" dia., with scribe marks S BT visible on partially healed blaze.
A fir, 14" dia., bears N.87½°W., 42 lks. dist., with healed blaze.
and a bearing tree mkd by James W. Byron, Deputy Co. Surveyor in 1963
A fir, 15" dia., bears N.86°E., 44 lks. dist., with scribe marks T29S R5W S36 CS BT visible on partially healed double blaze.

FD. Ok by Ken Hoffine, 1/2006 - M149-60

Ken Hoffine - For: Lone Rock Timberland Co. - Feb. 2017 - C.S. File 65/95-31

Found - 1957 BLM Brass Cap.
27" D.Fir bears N.85°E., 28.4 ft. (Rec. from BLM Field notes (DCS0) Pg 15514 N.87½°W., 27.72 ft). healed face and tag.
Record BT at N.86°E., 29.04 ft is blown over & uprooted.
New - 35" D.Fir bears N.69¾°W., 49.6 ft. We scribe T29S R5W S35 BT and tag tree.
Note - Found 1957 BLM BC at ground level with a metal fence post approx. 1.0 ft. north of corner. Corner lays approx. 400 ft. west of 30-5-1.0 RD and S.89°31'40"W., 347.1 ft. from the closing corner for Secs. 1 & 2 T30S R5W.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2795, surveyed July/Aug. 2015- (DCS0 records Vol. 59 Page 23569)

The cor of secs 35 & 36 only, on the S bdy of the Tp monumented with an iron post, 2½" dia., firmly set, projecting 2" above ground, with brass cap (properly) mkd. from which the remains of the bearing trees mkd. by Zirpel in 1957 and reported by Roseberry and Jelley in 1967-69
continued next page

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 574700

PRIMARY CORNER DESCRIPTION Sec. Cor. 35 & 36 only, T29-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A root hole bears N.46°E., 49.5 ft.
A fir, 13" dia., bears N.87½°W., 27.7 ft., with a healed blaze.
and the bearing tree mkd. by Byron, County Surveyor, in 1963, reported by Roseberry and Jelley
A fir, 26" dia., bears N.86°E., 29.0 ft., with a healed blaze.
Corner is located on a W. slope.
From the corner
N., 2.0 ft., to fence line extending E. and W.