TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36 only

Alias Description
Alias Description
Alias Description
Alias Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7132)

---

Set a post at proper distance, for cor. of secs. 1, 2, 35 and 36, from which
A R.Fir 15" dia.,bears S.20°W., 14 lks.
A R.Fir 6" dia., bears S.30°E., 12 lks.
A R.Fir 36" dia., bears N.70°W., 30 lks.
A Laurel 8" dia., bears N.5°E., 23 lks.

BLM resurvey by Jelley, Roseberry, and Brooks, under Group #'s 320 and 614 - Surveyed June 1966/May 1968 (DCSO records, Vol. 35 Page 14357)

---

Point for the cor. of secs. 35 and 36 only, on the S bdy. of T30S R5W, at proportionate distance, based on the 1854 Ford record. There is no remaining evidence of the orig. corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T 30 S R 5 W
S 35|S 36
S 2
T 31 S R 5 W
1967

from which
A Fir 40" dia.,bears N.7¼°E., 100 lks. dist., mkd. T30S R5W S36 BT.
A Fir 8" dia., bears N.39¼°W., 149 lks. dist., mkd. T30S R5W S35 BT.

Cor. Fd. OK, BLM resurvey by Berry and Akin, 1972-73, Group #800 (DCSO records, Vol. 38 Page 15653)

DCSO-GIS Corner visitation - 7/19/2005 - Typed: 2/8/2011 - C.S. File 67/33-1

---

Monument - 2¼" Comment - (needs) rehab