

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 35 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7135)

-----  
Set  $\frac{1}{4}$  sec. post, from which  
A R.Fir 8" dia., bears S.35°W., 13 lks.  
A Laurel 6" dia., bears N.85°E., 10 lks.

BLM resurvey by Lynn Roseberry, under Group #'s 350 and 614 -Surveyed Sept. 1967 (DCSO records, Vol. 35 Page 14391)

-----  
Point for the  $\frac{1}{4}$  sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd:

$\frac{1}{4}$   
S 35 S 36  
T 30 S R 5 W  
1967

from which

A Fir 10" dia., bears N.46°E., 21 lks. mkd.  $\frac{1}{4}$  S36 BT.  
Fir 35" dia., bears N.60 $\frac{1}{2}$ °W., 76 $\frac{1}{2}$  lks. mkd.  $\frac{1}{4}$  S35 BT.