

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7139)

Set a post corner of secs. 11, 12, 13 & 14 from which
A B.Oak 8" dia., bears S.37°E., 17 lks.
A R.Fir 12" dia., bears N.50°E., 16 lks.
A R.Fir 12" dia., bears N.25°W., 20 lks.
A Laurel 18" dia., bears S.85°W., 31 lks.

GL0 resurvey by Oscar Thiel under Contract #658 dated May 21, 1896 (DCSO records, Vol. 17 Page 7164)

I begin at the cor. of secs. 11, 12, 13 and 14, which is a fir post 5" sq. which had fallen to the ground and which I reset 24" in the ground, which post was marked and witnessed as described by the surveyor general.

John H. Markham, Jr. - For: Stomar Lumber Co. - March 1958 - C.S. File 42/349-3

As determined by O.B.T.s:
16" Fir stump bears N.50°E., 10.5 ft., O.B.T. Fd. scribe.
15" Fir stump bears N.32°W., 13.2 ft., O.B.T. Fd. scribe
At corner point, Set 1½" x 40" Iron pipe, from which
5" Laurel bears N.32°W., 11.6 ft. mkd. S11 BT.
12" Fir bears N.19°W., 24.5 ft. mkd. S11 BT.
10" Fir bears N.10°E., 21.0 ft. mkd. S12 BT.
30" Fir bears S.20°W., 35.4 ft. mkd. S14 BT.
Fence corner bears S.45°W., 16.5 ft. distance.

BLM resurvey by Lynn Roseberry & James Jelley, under Group #662 -Surveyed Oct. 1967/June 1969 (DCSO records, Vol. 38 Pages 15518-19)

From the Sec. cor. perpetuated and recorded by John H. Markham, Jr. in 1958, monumented with an iron pipe 1½" dia., firmly set, projecting 12" above ground, from which the remains of the original bearing trees:
A Fir root crown, bears N.50°E., 16 lks. dist., with a down decayed Fir stump alongside, 16" dia., with scribe marks BT visible on open blaze.
A Fir root crown, bears N.35°W., 20 lks. dist., with a down decayed Fir stump alongside, 15" dia., with scribe marks BT visible on open blaze. (Rec. N.25°W.)
and bearing trees mkd. by Markham:
(Cont. Next Page)

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. 11, 12, 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 11" dia., bears N.9°E., 32 lks. dist., with healed double blaze.

A Fir 31" dia., bears S.19°W., 53 lks. dist., with scribe marks S14 BT visible on bark blaze.

A Madrone 5" dia., bears N.32°W., 17½ lks. dist., with healed double blaze.

A Fir 13" dia., bears N.19°W., 37½ lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd:

T 30 S R 5 W
S 11 | S 12
S 14 | S 13
1969

from which a new bearing tree

A Fir 7" dia., bears S.77½°E., 29½ lks. dist., mkd.
T30S R5W S13 BT.

DCS0-GIS Corner visitation - 3/8/2004 - Typed: 2/8/2011 -
C.S. File 67/33-1

Monument - 2½" Comment - OK

fd. Ok by R. Brown 4/2007 - M152-68