

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Oscar F. Thiel, under Contract #658 dated May 21, 1896 (DCSO records, Vol. 17 Page 7165)

At a point, about 350 ft. above last branch, I set a Laurel post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd.: ¼ S on W. face, from which
A B.Oak 22" dia., bears S.5°W., 24 lks. mkd. ¼ S BT.
A Fir 7" dia., bears S.43¼°E., 8 lks., mkd. ¼ S BT.

A. R. Evans, Deputy Co. Surveyor - July/Aug. 1951 - C.S. File 45/69

Found scribed Laurel Post and Original BT:
7" Fir now 20", S.43¼°E., 8 lks., good condition.
Set ½" I.Pipe, with Fir stake alongside.

Doug. County Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel - July/Aug. 1963 - C.S. File 53/26-3

Found - 1/2" I.Pipe, 3" under.
Orig. 7" now 24" Fir S.43°E., 5.2 ft. This BT now face down.
Rotted base of large Oak that checks for Orig. SW BT
Set 3/4" Iron Rod alongside I.P.
New BTs -9" R.Fir bears S.73°W., 21.5 ft. scribed ¼ S11 CSBT.
10" Laurel, S.68°E., 54.5 ft. scribed ¼ S12 CS BT.

BLM resurvey by Lynn Roseberry & James Jelley, under Group #662 -Surveyed Oct. 1967/June 1969 (DCSO records, Vol. 38 Pages 15519-20)

The ¼ sec. cor. perpetuated and recorded by Evans, 1951, monumented with an iron pipe ½" dia., firmly set flush with ground, and subsequently perpetuated and recorded by Byron in 1963, with an iron rod, 3/4" dia., firmly set alongside projecting 10" above ground, from which the remains of the orig. bearing trees:
A root hole bears S.43¼°E., 8 lks., with a down and burned Fir alongside, 25" dia., no marks visible.
and bearing trees mkd. by Byron
A Madrone 12" dia., bears S.65½°E., 83½ lks., with scribe marks ¼ S12 CS BT visible on partially healed blaze.
A burned Fir snag, 10" dia., bears S.76°W., 32½ lks. with scribe marks ¼ S11 CS BT visible on opened double blaze.
(Cont. Next Page)

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

At the Corner Point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd:

T 30 S R 5 W

¼

S 11 | S 12

1969

from which a new bearing tree

A Madrone 21" dia., bears N.15¾°W., 124 lks., mkd. S11 BT.
Deposit iron rod alongside iron post.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician, under Group #1906, surveyed June/Aug. 1999. (DCSO rec. Vol. 53 page(s) 20517-8)

From the ¼ sec. cor. of secs. 11 & 12, monumented with an iron post, 2½" diam., firmly set, projecting 12" above ground, (with an iron rod, 5/8" diam., firmly set, projecting 14" above ground along side), with brass cap (properly) mkd. from which the remains of an original bearing tree

A root hole, bears S.43¾°E., 5.3 ft., with decayed fir alongside, size indeterminate, no marks visible.

and the remains of a bearing tree mkd. by Byron

A fir snag, 10" dia., bears S.74½°W., 20.9 ft., with a healed blaze. (Record, S.76°W., 21.5 ft.)

and a bearing tree mkd. by Roseberry and Jelley

A madrone, 26" dia., bears N.17½°W., 81.8 ft., with a healed blaze. (Record, N.15 ¾°W.)

and a new bearing tree

A madrone, 5" dia., the northern most of a double trunk bears S.86 ¾°E., 14.4 ft., mkd. 1/4 S12 BT.

Each new bearing tree has a 2½" X ¼" magnetic nail (Mag Nail) driven at the base on right side-center, unless otherwise described in the corner description.

David Edwards - For: Briggs Management LLC & Seneca Jones Timber Co. 7/2023 - C.S. file 65/112-001

Found - 9" dia., Madrone w/healed blaze bears S.86¾°E., 14.4'
27" dia., Madrone snag w/healed blaze bears N.17½°W.
81.8'

New - 11" dia., Madrone scribed "¼ S11 BT" bears N.78°W.,
20.3'
5.5 ft steel post is set N.89°W., 2 ft.