

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Oscar F. Thiel, under Contract #658 dated May 21, 1896 (DCSO records, Vol. 17 Page 7165)

-----  
A Maple tree, 5" dia., 200 ft. below top of ridge, which I mark for Cor. to Secs. 1, 2, 11 and 12, T30S S1 on NE., R5W S12 on SE., S11 on SW., S2 on NW sides, with 5 notches on S. and 1 notch on E. sides, from which

A Maple 15" dia., bears N.72°E., 55 lks. dist., mkd.  
T30S R5W S1 BT.

A Fir 24" dia., bears S.33°E., 24 lks. dist., mkd.  
T30S R5W S12 BT.

A Willow 5" dia., bears S.35°W., 31 lks. dist.,  
mkd. T30S R5W S11 BT.

A Fir 36" dia., bears N.31½°W., 33 lks. dist., mkd.  
T30S R5W S2 BT.

John H. Markham, Jr. - For: Stomar Lumber Co. - Witnesses:  
W.E. Crawford; R.G. Boyd; J.L. Markham - March 1958 - C.S.  
File 42/349-7

-----  
As determined by O.B.T.s:

15" Maple bears N.72°E., 36.3 ft., O.B.T.

38" Fir stump, logged, N.31½°W., 15.0 ft. O.B.T.

24" Fir stump, logged, S.33°E., 15.8 ft. O.B.T.

At Corner point Set 3/4" x 35" Iron pipe from which

4" Laurel bears S.11°E., 31.0 ft. mkd. S12 BT.

6" Cedar bears S.85°E., 25.7 ft. mkd. S1 BT.

14" laurel, N.57°E., 79.5 ft. mkd. S1 T30S R5W W.M. BT.

9" Maple bears N.6°W., 31.2 ft. mkd. S2 BT.

Road bears North 62.0 ft.

BLM resurvey by Lynn Roseberry & James Jelley, under Group #662 -Surveyed Oct. 1967/June 1969 (DCSO records, Vol. 38 Pages 15520-21)

-----  
The sec. cor. perpetuated and recorded by Markham, 1958, monumented with an iron pipe, 3/4" dia., firmly set, projecting 10" above ground, from which the remains of the original bearing trees:

A Maple 17" dia., bears N.72°E., 55 lks. dist., with healed blaze.

A burned Fir root crown 26" dia., bears S.33°E., 24 lks. dist., no marks visible.

A burned Fir stump 38" dia., bears N.31½°W., 23 lks. dist., no marks visible. (Rec. 33 lks.

and the remains of bearing trees mkd. by Markham:

(Cont. Next Page)

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A Cedar snag 8" dia., bears S.85°E., 38 lks. dist.,  
with healed double blaze.

A Maple 10" dia., bears N.6°W., 47½ lks. dist., with  
scribe marks S1 BT visible on partially healed double  
blaze.

At the Corner Point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the  
ground, directly over the iron pipe, with brass cap mkd:

T 30 S R 5 W

S 2 | S 1

S 11 | S 12

1969

from which a new bearing tree

A Cedar 8" dia., bears S.15 3/4°W., 287 lks. dist.,  
mkd. T30S R5W S11 BT.

No other trees available within limits.