

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Sec. Cor. for 1 and 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Oscar F. Thiel, under Contract #658 dated May 21, 1896 (DCSO records, Vol. 17 Page 7168)

-----  
Set a basalt stone 12x7x6 ins. 8" in the ground, for ¼ sec. cor., mkd. ¼ on W face, from which

A B.Oak 8" dia., bears S.12½°W., 220 lks. dist. mkd.

¼ S B T.

A B.Oak 24" dia., bears S.12½°E., 195 lks. dist., mkd.

¼ S B T.

A cold spring is 18 lks. NE from the SW bearing tree, along the W. slope through oak timber; slightly ascending ¼ sec. cor. is 200 ft. below top of ridge.

Doug. County Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel - July/Aug. 1963 - C.S. File 53/26-4

-----  
Found - Orig. SE BT, now snag, shows good scribing, checks record dist. & brg.

Orig. SW BT, alive, shows scribing, checks record dist. and brg.

Corner rock not found. Corner falls on open hillside. May have been cultivated at one time.

Set Brass cap at cor. mkd: County Surveyors Office, 1963

¼ S2|S1 T30S R5W

New BTs -14" R.Fir bears S.25°E., 87.0 ft. scribed ¼ S1 CSBT

10" R.Fir bears South, 102.0 ft. scribed ¼ S2 CSBT.

Corner found OK by BLM resurvey by Lynn Roseberry & James Jelley, under Group #662 -Surveyed Oct. 1967/June 1969 (DCSO records, Vol. 38 Pages 15523-24)

Fd. OK by W. Rogers, April 2000 - M134-52