

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7136)

-----  
Set ¼ sec.post at average distance, from which  
A Laurel 4" dia., bears N.85°W., 11 lks.  
A Laurel 5" dia., bears S.35°W., 9 lks.

H.L. Northcraft - T. Schatenkerk; H. Rishel; R. Wenuer - May 1950 - C.S. File 40/281

-----  
At proportionate distance between the SW corner of Sec. 25 and SE corner Sec. 25, 5,106.6 ft., we set a Madrone stake for corner mkd. ¼ S and set new witness trees:  
24" Fir N.15°E., 30 ft. ¼ S25 BT - 1581  
22" Fir S.13°E., 40 ft. ¼ S36 BT - 1581  
Corner located on North slope very near top of ridge in old burn.  
(These corners have A. Boyer's #1581, not authentic)

Doug. County Surveyors Office - James Byron, Deputy - Mike Darby; Jim Halterman - Nov/Dec 1963 - C.S. File 53/26-42

-----  
Found - Scribe stake at corner and both BTs except  
24" Fir bears N.18°E., 30.0 ft. not N.15°E. and  
SE BT is now a stump.  
Set Brass cap at cor. mkd: County Surveyor's ¼ S25 T30S R5W  
Office, 1963 S36  
New BT - 7" Laurel bears S.9°W., 32.7 ft. scribed ¼ S36 CSBT.

Fd. OK, by R. Brown, Oct. 1994 - M 120-78  
Fd. Ok by R. Brown, 3/2009 - M157-28