

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Sec. 1 only.

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6423)

Set ¼ sec. post at proper distance, from which
A Yellow Pine, 10" dia., bears S.15°W., 30 lks.
A Yellow Pine, 30" dia., bears N.27°E., 60 lks.

B.L.M. Survey by Lynn M. Roseberry and James E. Jelley, under Group #662. Surveyed Oct. 1967/June 1969) (DCSO records Vol. 38 Pages 15524 and 15525)

The point for the ¼ sec. cor. of sec. 1 only T. 30 S., R 5 W., is at proportionate distance on the N. bdy. of sec. 1. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

¼ S 1
T 30 S R 5 W
1969

from which
A fir, 13" dia., bears S.81¼°E., 52 lks., mkd. ¼ S1 BT.
A fir, 25" dia., bears S.16½°W., 71½ lks., mkd. ¼ S1 BT.
From this point, the cor. of Tps. 29 and 30 S., Rs. 4 and 5 W., bears N.89°38'E., 38.54 chs. dist.

FD. Ok by Ken Hoffine, 1/2006 - M149-60

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 2/23/2006 - C.S. File 67/14-7

Found - 3¼" dia., brass cap on 2½" dia., I.P. projects 5" above ground, firm (properly mkd)
13" Fir now 15" dia., x 5 ft. tall tin covered rotting stump healed single blaze visible bears S.81¼°E. 34.3 ft. (rec. S.81¼°E. 34.3 ft) 1969 BT
25" Fir now 23" dia., x 1½ ft. tall tin covered solid stump, low healed blaze visible, bears S.16½°W., 45.8 ft. rec. dist. measures well on slope. (Rec. S.16½°W., 47.2 ft.) 1969 BT.

New - 8" dia., D.Fir double blazed & scribed "T30S R5W ¼ S01 CS BT" bears S.71½°E., 11.7 ft.
8" dia., pine double blazed & scribed "T30S R5W ¼ S01 CS BT" bears S.47½°W., 22.5 ft.

6" dia., Pistol butt Maple double blazed & scribed "T30S R5W ¼ S01 CS BT" bears S.61¼°W., 47.6 ft.

Note - Corner lies 3 ft. south of E-W running fence line on gentle south facing slope.