

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24, 25; 19 & 30, T30-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - James Freeman under Contract #1 dated May 28, 1851
(DCSO records, Vol. 16 Page 6980)

Set post cor. of secs. 19, 24, 25 and 30, from which
A Yellow pine 10" dia., bears N.7°E., 475 lks.dist.
A Fir 10" dia., bears S.10°W., 250 lks.
A B.Oak 10" dia., bears S.5°E., 815 lks.
Impracticable to make trench.

GLO resurvey by Wm. Thiel under Contract #535 dated Feb. 5,
1889 (DCSO records, Vol. 17 Page 7013)

The post for this corner has been replaced by a small peg,
set probably by the County Surveyor, but all bearing trees
are still standing. I restore this corner by setting a
Laurel post, 4½ ft. long, 4" sq., 24" in the ground, marked
T30S S19 on NE., R4W S30 on the SE., R5W S25 on SW., S24 on
NW. faces, with 4 notches on N and 2 notches on S. edges,
from which
A Yellow pine 20" dia., bears N.7°E., 475 lks. dist., mkd.
T30S R4W S19 BT.
A Fir 20" dia., bears S.10°W., 250 lks. dist. mkd.
T30S R5W S25 BT.
A B.Oak 18" dia., bears S.5°E., 815 lks. dist., marked
T30S R4W S30 BT.
These are the original bearing trees which marks having
overgrown, I re-mark.
A Fir 10" dia., bears N.34¼°W., 10 lks. dist. marked
T30S R5W S24 BT.

Ben B. Irving, D.C.S. - Wit: Herbert Beyers; Mc Untington
Jan. 27, 1930 - C.S. File 5/44; & "old" cor. Bk. Pg. 201

Location identified from Pine N.7°E., 475 lks. and Fir
N.34½°W., 10 lks. (recorded S.34½°W.)
Set 4" x 6" x 22" hard sandstone, for corner, chisled 19 on
NE face; 30 on SE face; 24 on NW face and 25 on SW face.
Blazed and scribed:
16" Fir S.30°W., 58 lks. "T30S R5W S25 CS BT."
16" Fir S.35°E., 43 lks. "T30S R4W S30 CS BT".

Doug. County Surveyors Office - James Byron, Deputy - Mike
Darby; Wm. Stoffel - July 27, 1963 - C.S. File 53/26-78

Found - Stone at corner and all BTs as recorded. All are
now snags.
(Cont. Next Page)

