

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec Cor for 12 & 13; 7 & 18, of T30-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - James E. Freeman, under Contract #1 dated May 28, 1851 (DCSO records, Vol. 16 Page 6979)

Set post cor. of secs. 7, 12, 13 and 18, from which
A B.Oak 12" dia., bears N.74°E., 18 lks.
A W.Oak 7" dia., bears S.34°E., 54 lks.
A B.Oak 12" dia., bears S.76½°W., 14 lks.
A B.Oak 12" dia., bears N.37°W., 70 lks.

GL0 resurvey by Wm. Thiel under Contract #535 dated Feb. 5, 1889 (DCSO records, Vol. 17 Pages 7010-11)

The post being gone, but all bearing trees still standing, I replace the cor. by setting a Pine post, 4½ ft. long 4" sq., 24" in the ground, marked T30S S7 on NE., R4W S18 on SE., R5W S13 on SW., S12 on the NW. faces, with 2 notches on N. and 4 notches on S. edges, from which
A B.Oak 14" dia., bears N.74°E., 18 lks. dist., mkd. T30S R4W S7 BT.
A W.Oak 9" dia., bears S.30°E., 54 lks. dist., mkd. T30S R4W S18 BT.
A B.Oak 14" dia., bears S.76½°W., 14 lks. dist., mkd. T30S R5W S13 BT.
A B.Oak 13" dia., bears N.37°W., 70 lks. dist., mkd. T30S R5W S12 BT.

A.R. Evans, Deputy Co. Surveyor - July/Aug. 1951 - C.S. File 45/69

Set 5/8" I.Rod from 2 original BTs.
Blazed and scribed new BTs:
30" Fir N.34°E., 27.5 ft. mkd. T30S R4W 5 - 7 CSBT
10" Pine N.22°W., 18.1 ft. mkd. T30 R5 S12 CS BT.
20" Pine S.15°E., 33.7 ft. mkd. T30 R4 S18 CS BT.

Doug. County Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel - July/Aug. 1963 - C.S. File 53/26-96

Found - 3/4" I.Rod at corner and all bearing trees as recorded by Evans, except we find 20" Pine S.5°E., not S.15°E., 33.7 ft.
Rescribe now 19" B.Oak S.76½°W., 10.7 ft. S13 T30S R5W CSBT
We find old scribing on original NE bearing tree.

continued next page

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec Cor for 12 & 13, 7 & 18; of T30-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, and Robert Browning, Surveying Technician, under Group #1686, surveyed May 1993 thru April. 1995 - (DCSO records Vol. 52 Page(s) 20120-1)

The cor. of secs. 7, 12, 13 & 18, on the W. bdy. of the Tp., perpetuated by Evans, in 1951, further perpetuated by Byron, in 1963, monumented with an iron rod, 5/8" diam., firmly set, projecting 3" above ground, from which the remains of the original bearing trees:

A decayed oak, 18" diam., bears N.74°E., 18 lks., no marks visible.

An oak, 21" diam., bears S.76½°W., 14 lks., with healed triple blaze.

and the remains of bearing trees mkd. by Evans

A sawed fir stump, 31" diam., bears N.28½°E., 41 lks., with scribe marks BT visible on the bark.

A sawed pine stump, 25" diam., bears S.9½°W., 50 lks., with healed blaze.

A pine, 13" diam., bears N.17¼°W., 27 lks., with scribe marks T S R5W S visible on the bark.

At the corner point

Set a stainless steel post, 28" long, 2½" diam., 24" in the ground, directly over the iron rod, with brass cap mkd.

T30S
R5W R4W
S 12 | S 7
S 13 | S 18
1994

from which new bearing trees

A madrone, 11" diam., bears N.10½°E., 166 lks., mkd. T30S R4W S7 BT.

A madrone, 14" diam., bears S. 50¼° E., 12½ lks., mkd. T30S R4W S18 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

DCSO-GIS Corner visitation - 3/11/2004 - Typed: 2/8/2011 - C.S. File 67/33-1

Monument - 2½" IP/BC

Comment - OK

Fd. BC per rec - 2/2024 - B Heichel - M185-2