

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 7 only, T30-4

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - James E. Freeman, under contract #1 dated May 28, 1851 (DCSO records, Vol. 16 Page 6979)

Set ¼ sec. post, from which
 A Laurel 9" dia., bears S.78°E., 160 lks. dist.
 A W.Oak 8" dia., bears S.40°W., 87 lks. dist.

GLO resurvey by Wm. Thiel, under Contract #535 dated Feb. 5, 1889 (DCSO records, Vol. 17 Page 7010)

The cor. post having been destroyed, I set a Laurel ¼ sec. post, 3 ft. long, 3" dia., 24" in the ground, mkd: ¼S on W. face, from which
 A Laurel 12" dia., bears S.78°E., 160 lks. dist., mkd. ¼S BT, which I re-mark.
 A W.Oak 8" dia., bears S.40°W., 87 lks. dist., mkd. ¼S BT, is standing, but deadened by fire. I replace by a W.Oak 4" dia., bears S.40°W., 87 lks. mkd. ¼ S BT, a good sprout of the former bearing tree.

A.R. Evans, Deputy Co. Surveyor - July/Aug. 1951 - C.S. File 45/69

Set 5/8" Iron rod by proportional measurement.
 Blazed and scribed:
 20" Fir N.40°E., 23.2 ft. mkd. ¼ S7 T30 R4 R.E. 2741 CSSBT
 14" Fir N.29°W., 23.0 ft. mkd. ¼ S12 T30 R5 RE 2741 CSBT.

BLM resurvey by Roseberry and Jelley under Group #662 - Surveyed Oct. 1967/June 1969 (DCSO records, Vol. 38 Page 15509)

The ¼ corner re-established by A.R. Evans, 1951, monumented with an iron rod 5/8" dia., firmly set, projecting 4" above ground, from which the remains of bearing trees mkd. by Evans:
 A Fir stump 20" dia., bears N.40°E., 35 lks. dist., no marks visibile.
 A root hole bears N.29°W., 35 lks. dist., with a down fir stump alongside 14" dia., with scribe marks BT visible on bark blaze.

At the corner point
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd:

¼ S 7
 T 30 S
 R 4 W

1969

(Cont. Next Page)

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 700542

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 7 only, T30-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which new bearing trees
A Madrone 9" dia., bears N.68½°E., 111½ lks. dist., mkd
¼ S7 BT.
A W.Fir 9" dia., bears S.23 3/4°E., 264 lks. dist.,
mkd. ¼ S7 BT.