

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7 only, T.30-4

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - James E. Freeman under Contract #1 dated May 28, 1851 (DCSO records, Vol. 16 Page 6979)

-----  
Set post cor. of secs. 1, 6, 7 and 12, from which  
A Laurel 12" dia., bears N.3°W., 150 lks.  
A B.Oak 8" dia., bears S.46°W., 57 lks.  
A B.Oak 12" dia., bears N.69°E., 60 lks.  
A Fir 8" dia., bears S.37°E., 50 lks.

-----  
GLO resurvey by Wm. Thiel, under Contract #535 dated Feb. 5, 1889 (DCSO records, Vol. 17 Page 7009-10)

-----  
Intersect S. Bdy. of Sec. 6, 12 lks. East of Cor. of Secs. 1, 6, 7 and 12. No post being found, I restore the corner by setting Black Oak post, 4½ ft. long, 4" sq., 24" in the ground, mkd: T30S R6W on NE., R4W S7 on SE., R5W S12 on SW., S1 on NW. faces, with 1 notch on N., and 5 notches on S. edges, from which  
A Laurel 16" dia., bears N.3°W., 150 lks. dist., mkd. T30S R5W S1 BT.  
A B.Oak 10" dia., bears S.46°W., 57 lks. dist., mkd. T30S R5W S12 BT.  
A B.Oak 14" dia., bears N.69°E., 60 lks. dist., mkd. T30S R4W S6 BT.  
A Fir 12" dia., bears S.37°E., 50 lks. dist., mkd. T30S R4W S7 BT.

All original bearing trees, which I re-mark.

-----  
Ben B. Irving - Wit: L.H. Smick; Huron Clough; J.L. Worthington - Feb. 5-7, 1927 - C.S. File 3/63; Vol. 3 Pg. 273

-----  
I identify the location of this corner by four BTs which with one exception check with the gov't field notes. The only exception is that a Fir was recorded as S.37°E. and I found it to be S.22°E. For this corner, I set a ½" x 2" x 20" Iron bar 18" in the ground and an Oak Post, 4" x 4" x 6".

-----  
A.R. Evans, Deputy Co. Surveyor - July/Aug. 1951 - C.S. File 45/69

-----  
Found - ½" x 2" Iron bar and 4 orig. BTs.  
Blazed and scribed new trees:  
20" Fir N.25°E., 34.0 ft. mkd. T30S R4W S6 CS BT.  
30" Y. Fir S.35°E., 29.0 ft. mkd. T30 R4 S7 CS BT.

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7 only, T30-4

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Doug. County Surveyors Office - James Byron, Deputy - Aug. 1963 (added 3/16/2017) - C.S. File 53/26-97

-----


Found - 1" IP at cor. & alongside L.Bar  
 20" R.Fir, bears N.29°E., not N.25°E., 34.0' shows good scribing  
 30" R.Fir bears S.30°E., not S.35°E., 30.0'  
 We also find all orig. BTs or parts there of.

Bureau of Land Management resurvey by Roseberry and Jelly, under Group #662 - Surveyed Oct. 1967/June 1969 (DCSO records, Vol. 38 Page 15510)

The Sec. cor. perpetuated and recorded by A.R. Evans, 1951, monumented with an iron bar, ½ x 2 ins., firmly set, flush with ground, from which the remains of the original bearing trees:

- A root hole, bears N.69°E., 60 lks. dist., with a down oak stump alongside, 14" dia., with scribe marks T30S R4W S6 visible on open blaze. This tree was rescribed by Wm. Thiel in 1889.
  - A root hole, bears S.46°W., 57 lks. dist., with a down oak stump alongside, 10" dia., no marks visible on decayed blaze.
  - A Madrone 27" dia., bears N.3°W., 150 lks. dist., with scribe marks 3 5 1 visible on partially healed blaze. This tree was rescribed by Wm. Thiel in 1889.
- and bearing trees mkd. by Evans
- A Fir 25" dia., bears N.28½°E., 52 lks. dist., with scribe marks T30S R4W S6 CS BT visible on bark blaze.
  - A Fir 33" dia., bears S.31¼°E., 44 lks. dist., with scribe marks T30S R4W S7 CS BT visible on bark blaze.

At the corner point  
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:



Deposit iron bar alongside iron post.

Fd. & used by Ronald Quimby - April 1999 - M 129-44