

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 700643

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 6 only, of T30-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - James E. Freeman, under Contract #1 dated May 28, 1851 (DCSO records, Vol. 16 Page 6979 and 6981)

Set ¼ sec. post, from which
A Laurel 8" dia., bears N.37°E., 162 lks.
A B.Oak 7" dia., bears N.20°W., 43 lks.

GL0 resurvey by Wm. Thiel, under Contract #535 dated Feb. 5, 1889 (DCSO records, Vol. 17 Page 7009)

I restore this cor. by setting a Laurel post, 3 ft. long, 3" sq., 24" in the ground, mkd. ¼ S on W. face, from which
A Laurel 14" dia., bears N.37°E., 162 lks. mkd. ¼ S BT.
A B.Oak 9" dia., bears N.20°W., 43 lks. mkd. ¼ S BT.
These are the old bearing trees, which I re-mark, as the old marks are dim and overgrown.

John H. Markham, Jr. - Wit: Dennis & Geo. Vaughn - July 21, 1951 - C.S. File 40/179-4

Determined by O.B.T.:
A B.Oak 10" dia., bears N.20°W., 280 ft., found scribe.
At corner point, Set 1" x 30" Iron pipe, from which
A Fir 36" dia., bears N.81°W., 10.0 ft. mkd. ¼S S1 BT.
A Laurel 10" bears N.29°E., 18.0 ft. mkd. ¼S S6 BT.
This corner lies on top of a spur ridge on the West edge of a large opening.

BLM resurvey by Roseberry & Jelley, under Group #662. Surveyed Oct. 1967/June 1969 (DCSO records, Vol. 38 Page 15511)

Found corner as perpetuated by Markham, from which the remains of the original bearing tree:
A decayed B.Oak snag 12" dia., bears N.24½°W., 43 lks. with axe marks visible on decayed blaze. (Rec. N.20°W.) and bearing trees mkd. by Markham:
A Madrone 15" dia., bears N.29°E., 29½ lks., with scribe marks S S6 visible on bark.
A Fir 37" dia., bears N.76°W., 17½ lks. dist., with scribe marks BT visible on bark blaze.
At the corner point
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd:
(Cont. Next Page)

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 700643

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 6 only, T 30-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>T 30 S ¼ S 6 R 4 W 1969 from which a new bearing tree A Fir 37" dia., bears N.83¼°E., 32 lks. dist. mkd. ¼ S6 BT</p>
Fd. & used by Ronald Quimby - April 1999 - M 129-44