

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 037010

PRIMARY CORNER DESCRIPTION NW Cor. Cowles DLC #37

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Bowman and Burnett under contract dated Sept. 24, 1855

-----  
Set a post, marked, from which  
A B.Oak 12" dia., bears S.49°E., 71 lks.

Douglas Co. Surveyors Office - Ben B. Irving, Deputy - Wit: L.H. Smick; N.E. Richardson; Allen Moore - April/May 1929 - C.S. File 1/65 A&B; M 1-61 and "old" Cor. Bk. Pg. 183

-----  
**Note:** The records of corner descriptions of the Public Survey office at Portland does not agree with corners as found on ground. Remainder of field notes check reasonably close. After consultation with Dist. Attorney and Co. Surveyor and in view of the fact that no corners in field checked records and that age of corners corresponded with original work, it was decided to use field corners as the true corner and they are renewed accordingly.

-----  
Position identified from O.B.T. which we chopped out. There is not doubt as to its being the original BT although it contains no scribe marks.  
Drive 3/4" x 36" Galv. I.Pipe for corner, from which  
B.Oak 18" dia., bears S.49°E., 71 lks. O.B.T.  
Fir 22" dia., bears N.15°W., 20 lks. scribed Cl. 37 CSBT

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Jim Halterman - Jan. 1964 - C.S. File 53/40-13

-----  
Found - 3/4" I.P. at corner and under old E-W fence.  
Now 30" Fir stump N.15°W., 13.2 ft. shows good bark scribing "B"  
S.E. BT down.  
New BTs -17" B.Oak bears S.34°E., 62.9 ft. scribed NW DLC 37 CSBT.  
15" maple bears N.60°E., 7.0ft. scribed NW DLC 37 CS BT.  
10" R.Fir bears N.82°E., 36.4 ft. scribed NW DLC 37 CS BT.

Fd. OK by M. Heimbürger, July 1999 - M132-7  
Fd. OK by M. Heimbürger, July 2000 - 2000-0084 a & b  
Fd. IP by G. Lang, May 2011, M162-47