

PRIMARY CORNER DESCRIPTION SW Cor. Cowles DLC #37

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Bowman and Burnett under contract dated Sept. 24, 1855

Set post, marked as per instructions, from which
A W.Oak 8" dia., bears N.51°E., 172 lks. dist.

Douglas Co. Surveyors Office - Ben B. Irving, Deputy - Wit: L.H. Smick; N.E. Richardson - April/May 1929 - C.S. File 1/65 A & B; M 1-61; "Old" cor. Bk. Page 183 (See also, C.S. File 41/397)

Note: The records of corner descriptions of the Public Survey office at Portland does not agree with corners as found on ground. Remainder of field notes check reasonably close. After consultation with Dist. Attorney and Co. Surveyor and in view of the fact that no corners in field checked records and that age of corners corresponded with original work, it was decided to use field corners as the true corner and they were renewed accordingly.

Set from NW Corner of DLC 52 and NW corner of Cl. 37. Drove 1" x 18" shaft 6" underground in mound of rock, from which
A W.Oak 12" dia., bears S.75°W., 70 lks. blazed and scribed S.W. Cor. Cl. 37 C.S.B.T.
A W.Oak 10" dia., bears S.80°E., 27 lks. blazed and scribed S.W. Cor. Cl. 37 C.S.B.T.

Douglas Co. Surveyors Office - James Byron - Mike Stone and Jack Heritage - April 7, 1966 - C.S. File 53/117

WITNESS COR. FOR SW COR. DLC # 37
DLC Cor. to be covered for storage area.
Found - 1" steel shaft and BTs.
Set Brass cap, Wit. Cor. for SW. cor. DLC #37, mkd. "County Surveyors Office 1966 W.C. 207' West to SW Cor. DLC 37 T30S R6W".
New BTs -7" laurel bears S.20°W., 34.3 ft. scribed WC SW DLC 37 CS BT.
10" B.Oak bears N.36°E., 22.0 ft. scribed WC SW DLC 37 CS BT.