TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 040040

PRIMARY CORNER DESCRIPTION SE Cor. Catching DLC #40

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Bowman and Burnett under contract dated Sept. 24, 1855 DCSO DLC records pg 663

Set post for N W corner from which

Set a post for S E corner, from which
A W.Oak 10" dia., bears S.66°W., 35 lks.
A B.Oak 18" dia., bears N.35°W., 23 lks.

John Markham, Jr. - For: Harry Dayton - Oct. 16, 1952 - C.S. File 41/78-2

At a point 158.0 ft. south of the SW corner of DLC. #41, I set a ½" x 12" Iron pipe for corner point. From which
A W.Oak 16" dia., bears S.66°W., 23.0 ft. (This fits OBT description exactly but I could not find scribe) I remarked this tree Cl. 40, BT.
A W.Oak 24" dia., bears N.78°W., 133.5 ft mkd. D.L.C. No. 40 BT.
There is a fence running North and South from corner.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Jim Halterman - Jan. 1964 - C.S. File 53/40-21

Found - Both BTs as recorded by Markham. Also ½" I.P. at corner
Set Brass cap at cor. mkd: S.E. DLC 40 T30S R6W
County Surveyors Office 1964
No new bearing trees scribed.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 4/24/2002 - C.S. File 66/32-35

Found - 1964 DCSO brass cap/iron pipe protrudes 10" out of ground, 1 ft. west of N-S fence line.
10" now 21" dia., W.Oak shows healed previously opened blaze bears S.66°W., 23.1 ft. OBT
24" now 24" dia., 1 ft. high W.Oak stump no marks visible bears N.76¼°W., 133.5 ft. (rec. N.78°W., 133.5 ft.) 1952
DCSO brass cap iron pipe SW cor. DLC 41 bears North 158.0 ft.
New - 13" dia., W.Oak single blazed 4½ ft. above ground & scribed "X CS BT" bears South 18.5 ft. This tree is at 4-way fence corner.
23" dia., W.Oak double blazed & scribed "SE DLC 40 CS BT" bears N.41°E., 12.0 ft.
Compass decl. 17½°E._____