

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 041030

PRIMARY CORNER DESCRIPTION SW Cor. Wilson DLC #41

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Bowman and Burnett under contract dated Sept. 1855  
-----  
Set a post for S W corner from which  
A B.Oak 15" dia., bears S.25°E., 111 lks.  
A W.Oak 4" dia., bears N.45°E., 90 lks.

John H. Markham, Jr. - For: Harry Dayton - Oct. 16, 1952 -  
C.S. File 41/78-3  
-----  
Determined by O.B.T., a B.Oak 20" dia., bears S.25°E., 73.0  
ft., I found scribe.  
At corner point, I set 3/4" x 12" Iron rod, from which  
A W.Oak 13" dia., bears N.16°E., 60.5 ft. mkd. D.L.C. 41  
T30S R6W BT.  
A W.Oak 14" dia., bears S.8°W., 92.5 ft. mkd. Cl. 41 2880  
BT.  
There is a fence running North and South from this corner.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike  
Darby; Jim Halterman -Jan. 1964 - C.S. file 53/40-21  
-----  
Found - Both bearing trees. Also find 3/4" I.Rod at corner.  
Set Brass cap at cor. mkd: County Surveyors Office, 1964  
T30S R6W S.W. DLC 41.

Fd. ok by Douglas Co. Surveyors Office - Randall Smith,  
Deputy - Stephen Flause - 4/24/2002 - CS File 66/32-35 (back)