

PRIMARY CORNER DESCRIPTION NNE Cor. Hawkins DLC #42

Alias 044060 Description SSE Cor. DLC #44
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Bowman and Burnett, under Contract dated Sept. 24, 1855

Set a post for NE corner, from which
An Ash 10" dia., bears S.64°E., 177 lks.
An Ash 10" dia., bears S.37°W., 372 lks. (Notes for Cl. #44 says 572 lks.)
No tree convenient on the claim.

Frank Cain - For: R. Everett - March 18, 1919 - Field Book 110 Page 18.

Reestablished as per old BT.
An Ash 10" dia., bears S.64°E., 1.77 ch.

Douglas Co. Surveyors Office - N.E. Richardson, deputy - M.E. Godfrey; L.S. Kershner; O.V. Logsdon - Nov. 10, 1947 - C.S. File 39/126 and M 12-77

Set a 1" x 30" I.P. with brass cap mkd. County Surveyor office SE DLC 44, 14" under ground.
Marked New BTs
10" Ash bearing S.10°W., 107.0 ft.
16" Ash bearing N.83½°E., 117.4 ft.
Statement by O.V. Logsdon:
O.V. Logsdon of Riddle Oregon first being duly sworn says that the stump shown to Deputy County Surveyor N.E. Richardson is the stump of the original bearing tree for the I.B. Nichols DLC No 44 T30S R6W W.M. and that he has been personally (sic) known this for over 61 years and that Frank Cain a former County Surveyor used said tree to re-establish this corner. (signed) O.V. Logsdon.
Subscribed and sworn to before me this 10 day of November 1947.

Fd. Iron pipe w/o brass cap, June 1995 by W.Ruppert M119-68
Fd. OK by R. Brown 3/2001 2001-0023 A & B

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - Sept 18, 2013 - C.S. File 67/40-7

Found - A 2½" dia., brass cap (properly mkd) on a 1" I.D. iron pipe is set plumb with top of brass cap 13" below ground surface. 1947
Also a 1" dia., iron pipe (of unknown origin) Set plumb with top of pipe 2" below ground surface; bears S.60°W., 0.35 ft. from above noted BC monument. This pipe was identified as the DLC corner in a survey filed as M119-68 in the DCSO records.
No evidence of OBTs. continued next page

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 042010

PRIMARY CORNER DESCRIPTION NNE Cor. Hawkins DLC #42

Alias 044060 Description SSE Cor. DLC #44
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A 10" ash now a 25" dia., ash with a fully healed double blaze is now part of a triple trunk ash; the root crown of which bears S.10 $\frac{3}{4}$ °W., 107.6 ft. (rec. S.10°W., 107.0 ft. is good to base of scribed trunk) 1947

A 16" ash now a 25" dia., ash with a partially healed double blaze (scribing no longer visible) is now part of a double trunk ash; the root crown of which bears N.84°E., 117.4 ft. (rec. N.83 $\frac{1}{2}$ °E., 117.4 ft. is good to base of scribed trunk) 1947

New - A 23" dia., W.Oak scribed "NNE DLC 42 CS" "BT" on a double blaze; bears S.41 $\frac{3}{4}$ °E., 154.6 ft.

A e" dia., iron rod set plumb with top flush with ground surface (see detail of survey M119-68); bears S.22 $\frac{3}{4}$ °W., 140.9 ft.

Note - Monument is in flat open pasture with scattered ash and some oak trees. A wood post and electric wire fence running N-S is west (approx.) 60 ft. from the corner.

Compass decl. 15 $\frac{1}{2}$ °E.