

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 043040

PRIMARY CORNER DESCRIPTION SE Cor. Catching DLC #43

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Bowman and Burnett under Contract dated Sept, 1855

Set a post for S E cor., from which
A B.Oak 18" dia., bears N.43°W., 28 lks.
A B.Oak 12" dia., bears S.54°E., 44 lks.

Frank Cain - For: Amspoker and Neuner - Jan. 16, 1923 - Field
Book 109 Pg. 43

Found the corner in bad shape and renewed it as follows:
Set an Iron pipe 1" dia., 30" long 22" in ground for the
corner, from which
A B.Oak 18" dia., mkd. C.S., C.43, bears S.54°E., 40½ lks.
A B.Oak 16" dia., mkd. C.S. C.43, T30S R6W S.25 bears
N.27°W., 42 lks.
Established in the presence of P.A. Wilson, C.E. Osborn and
G. Griggs.

Douglas Co. Surveyors Office - John Powell, Willie Penley and
J. Heritage - Dec. 8, 1970 - C.S. File 53/40-102

Found - No trace of I.P., buried in edge of skid road, under
large down tree.
16" now 18" B.Oak N.27°W., 27.7 ft. scribe visible
"43 RW" and other marks, burnt face.
18" B.Oak now stump, S.54°E., 26.7 ft. shows scar.
Set Brass cap at cor. mkd: County Surveyors T 30 S R 6 W
Office, 1970 S E
DLC 43/

New BTs -10" Laurel N.10°W., 21.6 ft. scribed "SE C 43 CSBT"
(N-S wire fence imbedded in BT)
6" D.Fir S.14°E., 51.2 ft. scribed "S E DLC 43 CSBT"
Brass cap set 1.0 ft. north of corner point due to down and
buried log.