

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 045040

PRIMARY CORNER DESCRIPTION SE Cor. Flint DLC #45

Alias <u>046020</u>	Description <u>WSW Cor. Burch DLC #46</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Bowman and Burnett under Contract dated Sept. 24, 1855

Set post for corner from which
An Ash 5" dia., bears N.33°W., 370 lks.
A W.Oak 10" dia., bears S.26°E., 858 lks.

W. F. Briggs, D.C.S. - Wit: R.L. Irving - June 14, 1892 (date of survey corrected 9/7/2006) - Vol. 1 Pg. 201

Original BT stump standing. Set Post. Made new BT:
A B.Oak 16" dia., bears S.24°E., 780 lks. mkd. "CL 45 & C1 46 CS" on top. Blaze "BT" on lower blaze.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - Aug. 28-29, 2006 - C.S. File 67/14-25

Looked for not found.
Position falls in flat pasture land with no fence corners nearby. Positions of 1855 & 1892 BTs fall to the South partway up hillside. Ash tree position fell in open pastureland to north.