

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 051060

PRIMARY CORNER DESCRIPTION SE Cor. Judd DLC #51

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original - Bowman and Burnett under Contract dated Sept. 24, 1855</p> <p>-----</p> <p>Set post for corner from which A W.Oak 24" dia., bears N.17°E., 33 lks. A B.Oak 18" dia., bears N.2°W., 62 lks.</p>
<p>Douglas Co. Surveyors Office - George Wenderoth, Deputy - For: G.d. Shake and F.E. Weaver - Wit: G.L. Worley - April, 1946 - C.S. File 38/244</p> <p>-----</p> <p>Set by measurement from corners of DLC #52 Set 1" square spike 18" long and marked the following BTs: 14" W.Oak N.66°45'E., 62.7 ft. 5" W.Oak S.26°00'E., 23.7 ft.</p>
<p>Douglas Co. Surveyors Office - James Byron, Deputy - M.Darby; Wm. Stoffel - June 4, 1963 - C.S. File 49/139-103</p> <p>-----</p> <p>Found - Both BTs as recorded by Wenderoth. BTs are to be removed by P.P. & L. at this time. Also find PK nail in paving at corner. New BTs -12" W.Oak bears S.47°W., 213.5 ft. scribed SE DLC 51 CS BT. 1" Iron rod bears South, 42.2 ft. See sketch in file.</p>
<p> </p>