

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 052020

PRIMARY CORNER DESCRIPTION NW Cor. Trimble DLC #52

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Bowman and Burnett under contract dated Sept. 1855

Set a post for N W Corner from which
 A W.Oak 12" dia., bears S.3°W., 130 lks.
 A W.Oak 15" dia., bears S.27°E., 144 lks.

Douglas Co. Surveyors Office - Ben B. Irving - Wit: L.H. Smick; N.E. Richardson - April/May 1929 - C.S. file 1/65 A&B; M 1-61 and "Old" cor. Bk. Pg. 183

Note: The records of corner descriptions of the Public Survey office at Portland does not agree with corners as found on ground. Remainder of field notes check reasonably close. After consultation with Dist. Attorney and Co. Surveyor and in view of the fact that no corners in field checked records and that age of corners corresponded with original work, it was decided to use field corners as the true corner and they were renewed accordingly.

Found a rail coupling (angle bar) and original BT.
Set as new BTs:
 W.Oak 30" dia., bears S.1°E., 126 lks. scribed NW Cor. Cl. 52 CS BT.
 B.Oak 25" dia., bears S.67½°E., 235 lks. scribed N.W. Cor. Cl. 52 C.S.B.T.
 W.Oak (?) dia., bears S.3°W., 130 lks. (Orig. BT).

Douglas Co. Surveyors Office - James Byron, Deputy - M. Darby; Wm. Stoffel - June 4, 1963 - C.S. File 49/139-104

Found - Angle Iron at corner and both BTs as recorded.
 30" W.Oak S.1°E., 83.2 ft. now stump.
New BT - 14" Cedar bears S.42°W., 4.3 ft. scribed NW DLC 52 CS BT.