

PRIMARY CORNER DESCRIPTION SW Tsp. Cor. (SW Cor. Sec. 31)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Volume 17 Page 7191)

Set post for cor. to Tps. 30 and 31, Rgs. 6 & 7, from which
A Laurel 6" dia., bears S.51°W., 27 lks. dist.
A Laurel 6" dia., bears S.60°E., 20 lks. dist.
A Laurel 8" dia., bears N.45°W., 200 lks. dist.
A Laurel 12" dia., bears N.38°E., 148 lks. dist.

Cor. Fd. and used in GLO survey by W.H. Byars, under Contract #448 dated June 13, 1882 (DCSO records, Vol. 19 Pg. 7956)

John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: J.R. Markham - July/Aug. 1961 - C.S. File 42/288-1

As determined by O.B.T.s
23" Laurel N.45°W., 134.0 ft.
24" Laurel snag N.38°E., 100.0 ft.
30" Laurel snag S.60°E., 18.0 ft.
At corner point, Set 3/4" x 30" I.Pipe, from which
8" Fir bears South 53.4 ft. mkd. "S6 X BT."
Large rock 6' x 6' x 10' bears S.18°W., 33.0 ft. at North face.
5" Fir S.85°W., 13.8 ft. mkd. "S1 BT".
6" Fir N.15°W., 9.0 ft. mkd. "S36 BT".
6" B.Oak N.72°E., 26.2 ft. mkd. "S31 BT".

BLM Resurvey by James Jelley, under Group #585 - Surveyed, July/Aug. 1965 (DCSO records, Vol. 33 Page 13815)

The Tsp. corner, perpetuated and recorded by Markham, 1961, monumented with an iron pipe 3/4" dia., loosely set, extending 18" above ground, from which the remaining original bearing trees:
A rotted Madrone stump 24" dia., bears N.36°E., 148 lks. dist., with old axe marks visible on section of blaze. (Rec. N.38°E.)
The rotted remains of a Madrone stump, size indeterminate bears S.51°W., 27 lks.
A Madrone 16" dia., bears N.45°W., 212 lks. dist., with opened and burned blaze. (Rec., 200 lks.)
and bearing trees mkd. by Markham:
A B.Oak 6" dia., bears N.72°E., 39½ lks. dist., with scribe marks CS visible on partly healed blaze.
A Fir 9" dia., bears South, 81 lks. dist., with healed double blaze.
A Fir 6" dia., bears S.85°W., 21 lks. dist., with healed double blaze. (Cont. Next Page)

PRIMARY CORNER DESCRIPTION SW Tsp. Cor. (SW cor. Sec. 31)

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

A Fir 7" dia., bears N.15°W., 13½ lks. dist., with healed double blaze.

At the Corner Point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd:

T 30 S
 R 7 W R 6 W
 S 36 | S 31
 S 1 | S 6
 T 31 S
 1965

from which a new bearing tree

A Fir 15" dia., bears S.11°E., 76 lks. dist., mkd. T31S R6W S6 BT.

Reset Iron pipe alongside the iron post.

Fd Brass cap OK, BLM resurvey by Jelley, Apr/Sept. 1969 (DCSO records, Vol. 35 Page 14498) and Fd. OK, June 1977, Vol. 41 Page 16257)

Fd. OK, June 1988 by H. Johnstone - M 106-52
 Fd. OK, July 1992, Mark Smalley, M 112-52

Fd. Ok by DCSO, Stephen Flauser & John Pike, 4/7/2004 C.S. File 67/6-13

BLM resurvey by Joel R Herzberg, Cadastral Surveyor under Group No. 2928 - surveyed July /Aug. 2018 - (DCSO records Vol. 59 Page(s) 23657-8

 The cor. of Tps. 30 and 31 S., Rs. 6 and 7 W., reported by Jelley in 1977, monumented with an iron post, 2½" dia., firmly set, projecting 3" above ground, with a brass cap (properly) mkd.

from which bearing trees reported by Jelley

A fir, 23" dia., bears S.11°E., 50.2 ft., with a healed blaze.

A fir, 18" dia., bears N.15°W., 8.9 ft., with a healed blaze.

and new bearing trees

A fir, 17" dia., bears N.41½°E., 29.2 ft., mkd. T30S R6W S31 BT.

A fir, 22" dia., bears S.67°W., 19.5 ft., mkd. T31S R7W S1 BT.

The iron pipe, 3/4 in. diam., reset alongside the cor. by Jelley in 1965 was found firmly set, projecting 1 in. above ground, on the SE side of the cor. and an iron pipe, 1/2 in. diam., of unknown origin, was found firmly set, projecting 2 ins. above ground, on the NW side of the cor. (Cont. Next pg)

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Tsp. Cor. (SW Cor. Sec. 31)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Corner is located on an E. facing slope.
The geographic position in NAD 1983 (2011)
Latitude: 42°54'49.00" N. Longitude: 123°27'59.34" W.